

# 2V0-641<sup>Q&As</sup>

VMware Certified Professional 6 – Network Virtualization Beta

## Pass VMware 2V0-641 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/2v0-641.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by VMware  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

If unicast mode is configured for the overlay transport in an NSX deployment, which two statements correctly define the network support that is required? (Choose two.)

- A. Configure NSX High Availability.
- B. Layer 2 switching support in the access and distribution layers
- C. Layer 3 switching support in the access and distribution layers
- D. Configure Jumbo Frame support

Correct Answer: CD

---

**QUESTION 2**

Which two characteristics of the underlying physical network does VMware NSX require for robust IP transport? (Choose two.)

- A. The physical network should provide scalable network I/O using Layer 2 Multipathing (L2MP) and Multichassis Link Aggregation (MLAG).
- B. The physical network should provide scalable network I/O using Equal Cost Multipathing (ECMP).
- C. QoS is not necessary since classification and marking will be done in the overlay.
- D. QoS classification and marking is required to provide end-to-end flow control.

Correct Answer: BD

---

**QUESTION 3**

Which two options are use cases of Layer 2 bridging in NSX for vSphere? (Choose two.)

- A. Extend the network security to physical devices in the physical network by use of the Distributed Firewall.
- B. Extend physical services to Virtual Machines in virtual network.
- C. Allow clustering of multiple NSX Managers in a single vCenter Server instance.
- D. Allow physical devices in the physical network to use the NSX Edge Gateway as a default router.

Correct Answer: BD

---

**QUESTION 4**

A company wants to deploy VMware NSX for vSphere with no PIM and no IGMP configured in the underlying physical network. This company also must ensure that non-ESXi hosts do not receive broadcast, unknown unicast or multicast

(BUM) traffic.

Which replication mode should the logical switches be deployed with?

- A. Unicast Replication Mode
- B. Multicast Replication Mode
- C. Hybrid Replication Mode
- D. Transport Zone Mode

Correct Answer: A

---

#### **QUESTION 5**

An administrator needs to verify which port the switch manager is using. Which command should be used?

- A. show controller-cluster status
- B. show controller-cluster core stats
- C. show controller-cluster connections
- D. show controller-cluster logical-switches

Correct Answer: C

[2V0-641 PDF Dumps](#)

[2V0-641 Exam Questions](#)

[2V0-641 Braindumps](#)