

2V0-641^{Q&As}

VMware Certified Professional 6 – Network Virtualization Beta

Pass VMware 2V0-641 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/2v0-641.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which option is VMware's best practice for the deployment of NSX Manager and NSX Controller components?

- A. Deploy the NSX Manager and NSX Controller components to a management cluster.
- B. Deploy the NSX Manager component to a management cluster and the NSX Controller components to a resource cluster.
- C. Deploy the NSX Controller components to a management cluster and the NSX Manager component to a resource cluster.
- D. Deploy the NSX Manager and NSX Controller components to a resource cluster.

Correct Answer: A

QUESTION 2

-- Exhibit -

role	port	listening	open conns
api provider	api/443	Y	2
persistence_server	server/2878	-	0
	client/2888	Y	0
	election/3888	Y	1
switch_manager	ovsmgmt/6632	Y	0
	openflow/6633	Y	0
system	cluster/7777	Y	1

-- Exhibit -

An administrator is troubleshooting a NSX controller cluster issue and runs the control-cluster command, as shown in the Exhibit.

What information can be determined from the output provided in the exhibit?

- A. This is the control cluster majority leader controller.
- B. There are two controllers in the cluster.
- C. This is not the control cluster majority leader controller.
- D. The persistence_server role is not functioning correctly.

Correct Answer: C

QUESTION 3

Which two characteristics of the underlying physical network does VMware NSX require for robust IP transport? (Choose two.)

- A. The physical network should provide scalable network I/O using Layer 2 Multipathing (L2MP) and Multichassis Link Aggregation (MLAG).
- B. The physical network should provide scalable network I/O using Equal Cost Multipathing (ECMP).
- C. QoS is not necessary since classification and marking will be done in the overlay.
- D. QoS classification and marking is required to provide end-to-end flow control.

Correct Answer: BD

QUESTION 4

Where are the distributed NSX firewall decisions logged?

- A. NSX Manager
- B. vCenter Server
- C. NSX Edge
- D. ESXi host

Correct Answer: D

QUESTION 5

An administrator enables the NSX Ticket Logger to track infrastructure changes. The administrator logs out for lunch, returns and logs back in to complete the task. What is the status of ticket logger when the administrator logs back in?

- A. The ticket logger still tracks changes until it is turned off by the administrator.
- B. The ticket logger is turned off.
- C. The ticket logger will prompt the user if they still want to continue tracking changes.
- D. The ticket logger will display an error.

Correct Answer: B

[Latest 2V0-641 Dumps](#)

[2V0-641 VCE Dumps](#)

[2V0-641 Practice Test](#)