

# 500-451<sup>Q&As</sup>

Enterprise Networks Specialization

## Pass Cisco 500-451 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/500-451.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



### QUESTION 1

In the Converged Access solution, how does the controller display the access point name when there is no existing configuration for the AP?

- A. AP+IP address dotted decimal, for example, AP10.10.1.1
- B. AP+Ethernet MAC Address, for example, AP44d3:ca42.4337
- C. AP+IP address in hex, for example, AP0A.0A.01.01
- D. AP+Base Radio MAC Address, for example, AP18.33.9d.f1.40.50

Correct Answer: B

---

### QUESTION 2

In the Cisco Unified Wireless Network infrastructure, which combination of devices and/or features best accomplishes high availability?

- A. backup controllers and client SSO
- B. backup controllers and LAG
- C. N+1 and client state replication
- D. N+1 and backup controllers

Correct Answer: A

---

### QUESTION 3

Within Cisco ISE, which persona or node handles RADIUS requests and the Sponsor and Guest portals?

- A. Policy Administration Node
- B. Guest Service persona
- C. Policy Service persona
- D. Monitoring persona

Correct Answer: C

---

### QUESTION 4

What is ISE profiling?

- A. a feature used to identify the endpoints based on network data obtained from a number of enabled probes

B. an ISE function used for applying security templates to endpoints when ISE is integrated with Cisco Prime Infrastructure

C. a dynamic policy feature that uses a number of enabled probes to apply the correct ACL to roaming wireless endpoints

D. a form used for self-onboarding of wireless devices

Correct Answer: A

---

#### QUESTION 5

When Cisco Catalyst 3850 Switches are implemented in a stack configuration, which command is used to verify the role of each switch in the stack, and what are the two roles supported?

A. show switch stack role; active/standby

B. show switch detail; active/standby

C. show switch member; master/member

D. show stack detail; master/member

Correct Answer: B

[Latest 500-451 Dumps](#)

[500-451 PDF Dumps](#)

[500-451 VCE Dumps](#)