

642-813^{Q&As}

Implementing Cisco IP Switched Networks

Pass Cisco 642-813 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4lead.com/642-813.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

😳 365 Days Free Update

800,000+ Satisfied Customers





QUESTION 1

Which private VLAN access port belongs to the primary VLAN and can communicate with all interfaces, including the community and isolated host ports?

- A. promiscuous port
- B. isolated port
- C. community port
- D. trunk port
- Correct Answer: A

QUESTION 2

When you design a switched network using VTPv2, how many VLANs can be used to carry user traffic?

- A. 1000
- B. 1001
- C. 1024
- D. 2048
- E. 4095
- F. 4096

Correct Answer: B

QUESTION 3

- How does VTP pruning enhance network bandwidth?
- A. by restricting unicast traffic across VTP domains
- B. by reducing unnecessary flooding of traffic to inactive VLANs
- C. by limiting the spreading of VLAN information
- D. by disabling periodic VTP updates
- Correct Answer: B



QUESTION 4

Refer to the exhibit.

SW-1#sh logging %SPANTREE-SP-2-RECV_PVID_ERR; Received BPDU with inconsistent peer Vlan id 1 on GigabitEthernet11/2 VLAN2013. %SPANTREE-SP-2-BLOCK_PVID_PEER: Blocking GigabitEthernet11/2 on VLAN0001. Inconsistent peer vlan.

A multilayer switch has been configured to send and receive encapsulated and tagged frames. VLAN 2013 on the multilayer switch is configured as the native VLAN. Which option is the cause of the spanning-tree error?

- A. VLAN spanning-tree in SW-2 is configured.
- B. spanning-tree bpdu-filter is enabled.
- C. 802.1q trunks are on both sides, both with native VLAN mismatch.
- D. VLAN ID 1 should not be used for management traffic because its unsafe.

Correct Answer: C

QUESTION 5

An access switch at a remote location is connected to the spanning-tree root with redundant uplinks. A network engineer notices that there are issues with the physical cabling of the current root port. The engineer decides to force the secondary link to be the desired forwarding root port.

Which action accomplishes this task?

- A. Change the link-type to point-to-point.
- B. Enable Rapid Spanning Tree to converge using the secondary link.
- C. Adjust the secondary link to have a lower priority than the primary link.
- D. Apply a BPDU filter on the primary interface of the remote switches.

Correct Answer: C

642-813 Practice Test

642-813 Study Guide

642-813 Braindumps



To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.pass4lead.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:



One Year Free Update



Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.



To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days

Money Back Guarantee

from the date of purchase



Security & Privacy

We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.

Any charges made through this site will appear as Global Simulators Limited. All trademarks are the property of their respective owners. Copyright © pass4lead, All Rights Reserved.