

642-813^{Q&As}

Implementing Cisco IP Switched Networks

Pass Cisco 642-813 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass4lead.com/642-813.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

Ferris Plastics, Inc. is a medium sized company, with an enterprise network (access, distribution and core switches) that provides LAN connectivity from user PCs to corporate servers. The distribution switches are configured to use HSRP to


provide a high availability solution.

DSW1 -primary device for VLAN 101 VLAN 102 and VLAN 105

DSW2 - primary device for VLAN 103 and VLAN 104

A failure of GigabitEthemet1/0/1 on primary device should cause the primary device to release its status as the primary device, unless GigabitEthernet1/0/1 on backup device has also failed.

Troubleshooting has identified several issues. Currently all interfaces are up. Using the running configurations and show commands, you have been asked to investigate and respond to the following question.



If GigabitEthemet1/0/1 on DSW2 is shutdown, what will be the resulting priority value of the VLAN 105 HSRP group on router DSW2?

B. 100

C. 150

D. 200



https://www.pass4lead.com/642-813.html

2022 Latest pass4lead 642-813 PDF and VCE dumps Download

Correct Answer: A

QUESTION 2

In a Cisco switch, what is the default period of time after which a MAC address ages out and is discarded?

A. 100 seconds

B. 180 seconds

C. 300 seconds

D. 600 seconds

Correct Answer: C

QUESTION 3

Ferris Plastics, Inc. is a medium sized company, with an enterprise network (access, distribution and core switches) that provides LAN connectivity from user PCs to corporate servers. The distribution switches are configured to use HSRP to provide a high availability solution.

DSW1 -primary device for VLAN 101 VLAN 102 and VLAN 105


DSW2 - primary device for VLAN 103 and VLAN 104

A failure of GigabitEthemet1/0/1 on primary device should cause the primary device to release its status as the primary device, unless GigabitEthernet1/0/1 on backup device has also failed.

Troubleshooting has identified several issues. Currently all interfaces are up. Using the running configurations and show commands, you have been asked to investigate and respond to the following question.

https://www.pass4lead.com/642-813.html

2022 Latest pass4lead 642-813 PDF and VCE dumps Download



What is the priority value of the VLAN 105 HSRP group on DSW2?

A. 50

B. 100

C. 150

D. 200

Correct Answer: B

QUESTION 4

An access switch has been configured with an EtherChannel port. After configuring SPAN to monitor this port, the network administrator notices that not all traffic is being replicated to the management server. What is a cause for this issue?

- A. VLAN filters are required to ensure traffic mirrors effectively.
- B. SPAN encapsulation replication must be enabled to capture EtherChannel destination traffic.
- C. The port channel can be used as a SPAN source, but not a destination.

https://www.pass4lead.com/642-813.html


2022 Latest pass4lead 642-813 PDF and VCE dumps Download

D. RSPAN must be used to capture EtherChannel bidirectional traffic.

Correct Answer: C

QUESTION 5

Refer to the exhibit.



Users of PC-1 experience slow connection when a webpage is requested from the server. To increase bandwidth, the network engineer configured an EtherChannel on interfaces Fa1/0 and Fa0/1 of the server farm switch, as shown here:

Server_Switch#sh etherchannel load-balance

EtherChannel Load-Balancing Operational State (src-mac):

Non-IP: Source MAC address

IPv4: Source MAC address

IPv6: Source IP address

Server_Switch#

However, traffic is still slow. Which action can the engineer take to resolve this issue?

- A. Disable EtherChannel load balancing.
- B. Upgrade the switch IOS to IP services image.
- C. Change the load-balance method to dst-mac.
- D. Contact Cisco TAC to report a bug on the switch.

Correct Answer: C

642-813 PDF Dumps

642-813 Study Guide

642-813 Braindumps



To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.pass4lead.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4lead, All Rights Reserved.