

HP0-Y52^{Q&As}

Applying HP FlexNetwork Fundamentals

Pass HP HP0-Y52 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hp0-y52.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which statement correctly defines the management capabilities of an HP MultiService Mobility (MSM) access point (AP)?

- A. The AP only supports controlled mode.
- B. The AP operates in autonomous mode by default, but can be changed to controlled mode.
- C. The AP operates in controlled mode by default, but can be changed to autonomous mode.
- D. The AP only supports autonomous mode.

Correct Answer: C

QUESTION 2

Which HP solution provides network optimization and automated network provisioning to its customers?

- A. Intelligent Management Center NTA
- B. FlexNetwork Architecture
- C. Intelligent Resilient Framework
- D. Software-defined Networking

Correct Answer: D

QUESTION 3

Exhibit1.



Exhibit 2

```
Switch-1(config)# show ip route
```

Destination	Gateway	Vlan	Type	Sub-Type	Metric	Dist.
10.0.1.0/24	VLAN101	101	connected		1	0
10.0.2.0/24	VLAN201	201	connected		1	0
10.1.10.0/24	VLAN10	10	connected		1	0
10.1.20.0/24	10.0.1.1	101	static		1	1
127.0.0.0/8	reject		static		0	0
127.0.0.1/32	lo0		connected		1	0

A network administrator wants to create a backup IP route to 10.1.20.0/24 on Switch-1. The backup route should use Link 2, and it should only be used if Link 1 is down. What is the correct setup to accomplish this?

- A. an IP route through 10.0.2.2 with administrative distance 1
- B. an IP route through 10.1.20.1 with administrative distance 1
- C. an IP route through 10.0.2.2 with administrative distance 10
- D. an IP route through 10.1.20.1 with administrative distance 10

Correct Answer: D

QUESTION 4

Refer to the exhibit.

```
[Comware] telnet server enable
[Comware] user-interface vty 0 15
[Comware-ui-vty0-15] authentication-mode password
[Comware-ui-vty0-15] set authentication password cipher password1
[Comware-ui-vty0-15] user privilege level 1
[Comware-ui-vty0-15] quit
[Comware] super authentication-mode local
[comware] super password level 3 cipher password2
```

An HP Comware switch is using its default user-interface settings. The network administrator then enters the commands shown in the exhibit. What correctly describes how an admin user must now log in?

- A. When the admin user logs in to the console port, the admin user must enter either a password of password1 or password2.
- B. When the admin user logs in using Telnet, the admin user must enter either a password of password1 or password2.
- C. When the admin logs in using Telnet, the admin user must enter a password of password1 and is given level 1 privileges.
- D. When the admin user logs in to the console port, the admin user must enter a password of password1 and is given

level 3 privileges.

Correct Answer: D

QUESTION 5

What does the traceroute command identify on an HP ProVision switch?

- A. each Layer 3 device between the switch and a destination
- B. the path to each router connected to the switch
- C. debug output tracing entries to the routing table
- D. each physical device between the switch and a destination

Correct Answer: B

[HP0-Y52 VCE Dumps](#)

[HP0-Y52 Practice Test](#)

[HP0-Y52 Braindumps](#)