

1Y0-230^{Q&As}

Citrix NetScaler 12 Essentials and Unified Gateway

Pass Citrix 1Y0-230 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/1y0-230.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which three NetScaler features can a Citrix Administrator use for default syntax policies? (Choose three.)

- A. SSL
- B. Rewrite
- C. Integrated caching
- D. Protection
- E. Responder

Correct Answer: ABE

Reference <https://docs.citrix.com/zh-cn/netscaler/11/appexpert/policies-and-expressions/ns-pi-intro-polexp-wrapper-con/ns-pi-adv-class-pol-con.html>

QUESTION 2

Which scenario will cause automatic high availability (HA) synchronization to fail?

- A. Different build versions
- B. A configuration change to the primary Citrix ADC
- C. A force failover
- D. Manually forced synchronization

Correct Answer: B

QUESTION 3

A Citrix Administrator needs to generate AppFlow data for internal ICA connections.

Which two connection methods could the administrator use to route internal ICA connections through NetScaler without modifying the existing network routing? (Choose two.)

- A. Policy-based Routing
- B. ICA Proxy
- C. SOCKS proxy
- D. Transparent Mode

Correct Answer: AD

QUESTION 4

A Citrix Administrator receives complaints from some users that authentication for the Citrix Gateway site fails.

Which tool can the administrator use to find data regarding time of failure and a list of users facing this issue?

- A. Gateway Insight
- B. Security Insight
- C. Web Insight
- D. HDX Insight

Correct Answer: D

QUESTION 5

Scenario: A Citrix Administrator has a NetScaler SDX appliance with several instances configured. The administrator needs one instance with two interfaces connected to forward packets that are NOT destined for its MAC address. Hence, the administrator has enabled Layer 2 mode. After enabling Layer 2 mode, the administrator found the interface status going up and down.

What can the administrator perform to resolve this issue?

- A. Disable Layer 2 mode on a NetScaler instance.
- B. Enable MAC-based Forwarding mode.
- C. Enable tagging on all interfaces.
- D. Enable Layer 3 mode along with Layer 2 mode.

Correct Answer: C

[1Y0-230 VCE Dumps](#)

[1Y0-230 Practice Test](#)

[1Y0-230 Study Guide](#)