

1Y0-240^{Q&As}

Citrix NetScaler Essentials and Traffic Management

Pass Citrix 1Y0-240 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/1y0-240.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which NetScaler mode is commonly referred to as `inline mode`?

- A. One-Arm Mode
- B. MAC-based Forwarding
- C. Two-Arm Mode
- D. Use Source IP (USIP)

Correct Answer: C

QUESTION 2

A Citrix Administrator needs to configure a rate limiting policy for the DNS requests to a threshold of 1000 DNS requests per second.

Which set of commands does the administrator need to run to correctly configure the rate limiting policy?

- A.

```
add stream selector DNSSelector1 client.udp.dns.domainadd ns limitIdentifier DNSLimitIdentifier1 – threshold 5 –timeSlice 1000 –selectorName DNSSelector1add dns policy DNSLimitPolicy1 “sys.check_limit(“DNSLimitIdentifier1”)” –preferredLocation “North America.US.TX.Dallas..”bind dns global DNSLimitPolicy1 5
```
- B.

```
add stream selector DNSSelector1 client.udp.dns.domainadd ns limitIdentifier DNSLimitIdentifier1 – threshold 5 –timeSlice 1000 –selectorName DNSSelector1add dns policy DNSLimitPolicy1 “sys.check_limit(“DNSLimitIdentifier1”)” –preferredLocation “North America.US.TX.Dallas..”
```
- C.

```
add stream selector DNSSelector1 client.udp.dns.domainadd ns limitIdentifier DNSLimitIdentifier1 – threshold 1000 –timeSlice 1000 –selectorName DNSSelector1add dns policy DNSLimitPolicy1 “sys.check_limit(“DNSLimitIdentifier1”)” –preferredLocation “North America.US.TX.Dallas..”
```
- D.

```
add stream selector DNSSelector1 client.udp.dns.domainadd ns limitIdentifier DNSLimitIdentifier1 – threshold 1000 –timeSlice 1000 –selectorName DNSSelector1add dns policy DNSLimitPolicy1 “sys.check_limit(“DNSLimitIdentifier1”)” –preferredLocation “North America.US.TX.Dallas..”bind dns global DNSLimitPolicy1 5
```

Correct Answer: C

QUESTION 3

Which feature can a Citrix Administrator use to create a consistent set of front-end SSL parameters across multiple SSL virtual servers?

- A. SSL Policy
- B. SSL Profile

- C. SSL Bridge
- D. SSL Offload

Correct Answer: B

QUESTION 4

Which two options should a Citrix Administrator consider when adding a secondary device in a high availability (HA) pair? (Choose two.)

- A. Configure the HA status of the Primary Node as STAYPRIMARY.
- B. HA Monitoring should be disabled on all the unused interfaces.
- C. Both the devices should have different SNIP addresses.
- D. The nsroot password should be the same on both nodes.
- E. The Independent Network Configuration (INC) mode should be enabled.

Correct Answer: BD

QUESTION 5

What are two advantages of using Content Switching for Global Server Load Balancing (GSLB) service selection? (Choose two.)

- A. Apply different load balancing methods on the different subsets of GSLB services in the deployment.
- B. Define a subset of GSLB services with different priorities and specify an order in which the services in the subset are applied to a request.
- C. Ability to bind multiple GSLB vServers with different protocol types under one Content Switching vServer.
- D. Bind multiple GSLB domains or FQDNs to a single GSLB vServer.

Correct Answer: BC

[Latest 1Y0-240 Dumps](#)

[1Y0-240 VCE Dumps](#)

[1Y0-240 Exam Questions](#)