

299-01^{Q&As}

Riverbed Certified Solutions Professional - Network Performance Management

Pass Riverbed 299-01 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/299-01.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Riverbed Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

What are the two (at a minimum) devices you need to configure in Cascade Profiler for Switch Port Discovery integration to work for a portion of the network?

- A. At least one NetFlow sources (router, switch, or steelhead).
- B. At least one lookup router and at least one access tier switch.
- C. A Vulnerability Scanner and a Netflow source (router, switch, or steelhead).
- D. A Vulnerability Scanner and an External Link.

Correct Answer: B

QUESTION 2

What are the two types of dashboards available within the Cascade Profiler GUI? (select 2)

- A. Top Hosts
- B. Top Applications
- C. Public
- D. Private
- E. Devices and Interfaces Utilization

Correct Answer: CD

QUESTION 3

Which of the following types of hosts are included in Cascade grouping on Cascade Profiler?

- A. Internal hosts only
- B. External hosts only
- C. All hosts
- D. Internal and External hosts only
- E. Specified internal hosts plus the non-routable subnets

Correct Answer: A

QUESTION 4

When using Network Performance Monitoring solutions the following statements are true. (select 2)

- A. HTTP Object load times can be analyzed with full packet capture
- B. SSL Decryption can be used without any special key imports provided the start of the TCP conversation is captured
- C. Software Agents are required on Servers in order to measure the Network Round trip time of applications
- D. ICMP (ping echo/response) must be used in order to measure Network Round Trip time
- E. NetFlow records can be summarized to provide utilization on a router interface

Correct Answer: AE

QUESTION 5

Filtering in Cascade Pilot: (Select 2)

- A. Is either a BPF or Wireshark Display filter only.
- B. Can be created from a chart.
- C. Can be changed after applying a View.
- D. Is the equivalent of the Wireshark "display filter input".

Correct Answer: BC

[Latest 299-01 Dumps](#)

[299-01 Exam Questions](#)

[299-01 Braindumps](#)