300-425^{Q&As}

Designing Cisco Enterprise Wireless Networks (ENWLSD)

Pass Cisco 300-425 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass2lead.com/300-425.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

A company has 10 access point licenses available on their backup Cisco WLC and their primary Cisco WLC is at full capacity, 5 access points are set to high failover priority and 7 access points are set to critical failover priority. During a failure, not all critical access points failed over to the backup Cisco WLC. Which configuration is the cause of this issue?

A. The high priority access point is oversubscribed.

B. network ap-priority is set to enable.

C. The critical priority access point count is oversubscribed.

D. network ap-priority is set to disable.

Correct Answer: D

Reference: https://www.ciscolive.com/c/dam/r/ciscolive/emea/docs/2016/pdf/BRKCOL-2275.pdf

QUESTION 2

A hospital wireless environment was designed with these characteristics: RF coverage better than -67 dBm in the 5 GHz spectrum RRM be used for DCA and TPC in the 2.4 GHz band RRM be used for DCA and TPC in the 5 GHz band

After deployment, why do many of the legacy 802.11b/g devices have difficulty maintaining connectivity?

A. Excessive co-channel interference in the 2.4 GHz band exists.

B. Excessive overlapping channels in the 2.4 GHz band exists.

C. TPC drastically increases Tx power in the 2.4 GHz band.

D. TPC drastically reduces Tx power in the 2.4 GHz band.

Correct Answer: D

QUESTION 3

A wireless consultant reviewing the installation of an old wireless network. The existing AireOS controllers are running software version 6.0.4539:44024. The customer is using OEAP and wants to keep this functionality. Which licenses should the consultant propose with the latest controller software version?

A. Base

B. Premium

C. WPlus

D. Advanced

![Pass2Lead](https://Pass2Lead.com)
Correct Answer: C

QUESTION 4

A customer has a Wi-Fi network that is designed to support video over Wi-Fi. The Wi-Fi network has good coverage; however, video multicast traffic is unreliable. Video multicast traffic is reliable on the wired portion of the network. Which performance value indicates an issue with the Wi-Fi multicast traffic?

A. jitter

B. packet error rate

C. throughput

D. latency

Correct Answer: B

QUESTION 5

A new wireless network design has these requirements: AireOS WLCs as guest anchors a Cisco Catalyst 9800 Series WLC as the foreign controller use of Wi-Fi 6 APs inter-controller roaming for guest users

Which two design approaches meet these requirements? (Choose two.)

A. Use EoIP for communication between controllers.

B. Use WLC software versions that support IRCM.

C. Use AVC on the anchor WLCs.

D. Use IPv6 across the wireless network.

E. Use secure mobility to pair controllers.

Correct Answer: BE

[300-425 VCE Dumps](https://www.pass2lead.com/300-425.html)   [300-425 Practice Test](https://www.pass2lead.com/300-425.html)   [300-425 Braindumps](https://www.pass2lead.com/300-425.html)