

# 300-435<sup>Q&As</sup>

Automating and Programming Cisco Enterprise Solutions (ENAUTO)

## Pass Cisco 300-435 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/300-435.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



### QUESTION 1

A network administrator must troubleshoot a network issue using Cisco DNA Center. Which API request helps to determine issue details, impacted hosts, or suggested actions for the resolution?

- A. /dna/intent/v1/issues
- B. /dna/intent/api/v1/issues
- C. /dna/intent/v1/issue-enrichment-details
- D. /dna/api/v1/client-health/issues

Correct Answer: B

The intent/api/v1/issues request determine issue details, hosts impacted and suggests actions for resolution.

---

### QUESTION 2

Which two API calls are used to trigger a device configuration sync in Cisco DNA Center? (Choose two.)

- A. PUT /dna/intent/api/v1/network-device
- B. PUT /dna/intent/api/v1/network-device/sync-all
- C. PUT /dna/intent/api/v1/network-device/{networkDeviceId}/sync
- D. PUT /dna/intent/api/v1/network-device/sync
- E. POST /dna/intent/api/v1/network-device/{networkDeviceId}/sync

Correct Answer: CE

Reference: <https://github.com/CiscoDevNet/DNAC-JAVA-SDK/tree/master/DnacAppApi>

---

### QUESTION 3

Which two Cisco DNA center features are needs to add legacy on the platform? (Choose two.)

- A. Multivendor SDK support
- B. Trusted device profile update
- C. Device package creation
- D. Device package download
- E. Device profile replication

Correct Answer: AD

---

**QUESTION 4**

With the MV Sense API, which REST endpoint provides LUX level?

- A. /merakimv/XXXX-XXXX-XXXX/light
- B. /merakimv/XXXX-XXXX-XXXX/raw\_detections
- C. /merakimv/XXXX-XXXX-XXXX/0
- D. /merakimv/XXXX-XXXX-XXXX/zones

Correct Answer: A

Reference: <https://developer.cisco.com/meraki/mv-sense/#!mqtt/lux-light-levels>

---

**QUESTION 5**

FILL BLANK

Fill in the blank to complete the URL for the Cisco SD-WAN API that retrieves a list of users that are logged into a device.

**http://<vmanage-ip-address>/dataservice/device/  deviceid=<deviceid>>**

- A. interface?

Correct Answer: A

Reference: [https://sdwan-docs.cisco.com/Product\\_Documentation/Command\\_Reference/Command\\_Reference/vManage\\_REST\\_APIs/Real-Time\\_Monitoring\\_APIs/Interface](https://sdwan-docs.cisco.com/Product_Documentation/Command_Reference/Command_Reference/vManage_REST_APIs/Real-Time_Monitoring_APIs/Interface)

[Latest 300-435 Dumps](#)

[300-435 Study Guide](#)

[300-435 Braindumps](#)