

300-815^{Q&As}

Implementing Cisco Advanced Call Control and Mobility Services
(CLACCM)

Pass Cisco 300-815 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/300-815.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which two configuration parameters are prerequisites to set Native Call Queuing on Cisco UCM? (Choose two.)

- A. Cisco IP Voice Media Streaming Service must be activated on at least one node in the cluster.
- B. A unicast music on hold audio source must be configured.
- C. Cisco RIS data collector service must be running on the same server as the Cisco CallManager service.
- D. The maximum number of callers allowed in queue must be 10.
- E. The phone button template must have the Queue Status Softkey configured.

Correct Answer: AC

Reference: https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/admin/12_0_1/systemConfig/cucm_b_system-configuration-guide-1201/cucm_b_system-configuration-guide-1201_chapter_01001101.html#CUCM_RF_C960BC9A_00

QUESTION 2

Which built-in bridge configuration option can be set on the individual IP phones to ensure that the cluster-wide service parameter is used?

- A. automatic
- B. default
- C. on
- D. off

Correct Answer: B

QUESTION 3

Which top-level IOS command is needed to begin the configuration of a Cisco Unified Communications Manager Express gateway to enable phones to be registered via SIP?

- A. allow-connections sip to sip
- B. voice service voip
- C. voice register global
- D. voice register dn

Correct Answer: B

Reference: <https://www.cisco.com/c/en/us/support/docs/voice-unified-communications/unified-communications-manager-express/99946-cme-sip-guide.html>

QUESTION 4

The screenshot shows the Cisco Unified CM Administration interface for configuring a SIP Route Pattern. The page title is "Cisco Unified CM Administration For Cisco Unified Communications Solutions". The navigation menu includes System, Call Routing, Media Resources, Advanced Features, Device, Application, User Management, Bulk Administration, and Help. The main content area has a toolbar with Save, Delete, Copy, and Add New buttons. Below the toolbar is a "Status" section with an information icon. The "Pattern Definition" section contains the following fields: Pattern Usage* (Domain Routing), IPv4 Pattern* (*.cms.domain.local), IPv6 Pattern (empty), Description (empty), Route Partition (internal-pt), SIP Trunk/Route List* (CMS-Cluster-RL), and a Block Pattern checkbox. The "Calling Party Transformations" section includes Use Calling Party's External Phone Mask (checkbox), Calling Party Transformation Mask (empty), Prefix Digits (Outgoing Calls) (empty), Calling Line ID Presentation* (Default), and Calling Line Name Presentation* (Default). The "Connected Party Transformations" section includes Connected Line ID Presentation* (Default) and Connected Line Name Presentation* (Default). At the bottom, there are Save, Delete, Copy, and Add New buttons, and a note: "i *- indicates required item."

Refer to the exhibit. The customer is troubleshooting an issue where users cannot dial the CMS SIP Route Pattern. The CMS URI they are attempting to dial is 7772002@cms.domain.local. Which IPv4 pattern must the customer enter to resolve the issue?

- A. 7772002@cms.domain.local
- B. *@cms.domain.local
- C. *.cms.domain.local
- D. cms.domain.local

Correct Answer: B

QUESTION 5

What are two configuration features of the Client Matter Code setting in the route pattern configuration? (Choose two.)

- A. The Client Matter Code feature does not support overlap sending since the Cisco UCM cannot determine when to prompt the user for the code.
- B. Selecting the Allow Overlap Sending setting disables the Require Client Matter Code setting.
- C. Selecting the Allow Overlap Sending setting allows a user to select the Require Client Matter Code setting.
- D. The Client Matter Code feature supports overlap sending since the Cisco UCM can determine when to prompt the user for the code.
- E. The Client Matter Code feature provides the option to configure Authorization Level such as in the Forced Authorization Code.

Correct Answer: AB

Reference: https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/admin/10_0_1/ccmfeat/CUCM_BK_F3AC1C0F_00_cucm-features-services-guide-100/CUCM_BK_F3AC1C0F_00_cucm-features-services-guide100_chapter_010000.pdf

[Latest 300-815 Dumps](#)

[300-815 Practice Test](#)

[300-815 Study Guide](#)