

31860X^{Q&As}

Avaya IX Calling Design

Pass Avaya 31860X Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/31860x.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

A customer has 80 remote users, and you expect 25% of the users will be connected at any one time using G.729. Assuming the following requirements:

a G.729 codec requires 30 kbps a G711 codec requires 80 kbps 720p HD video codec requires 512 Kbps

How much bandwidth is needed for a public interface WAN link of the centralized SBCE for the deskphones used by remote workers?

- A. 6400 Kbps
- B. 2400 Kbps
- C. 1600 Kbps
- D. 600 Kbps

Correct Answer: A

QUESTION 2

You are designing media gateways at remote locations for a customer. They have requested the following:

Analog telephone calls go through the PSTN in case of power outage. Redundant power supply The same administrative and telephone functionality during WAN outage

Which design meets these customer requests?

- A. A design with G450 gateways with dual power supplies, and Standard Local Survivability
- B. A design with G430 gateways with dual power supplies, and Standard Local Survivability
- C. A design with G450 gateways with dual power supplies, and S8300 Survivable-Remote
- D. A design with G430 gateways with dual power supply, and S8300 Survivable-Remote

Correct Answer: A

QUESTION 3

In an Avaya Aura 8.1 deployment, where do Remote SIP Workers ultimately register?

- A. Session Manager
- B. Communication Manager

C. Avaya Device Adapter

D. System Manager

Correct Answer: C

QUESTION 4

A customer has a main location and several remote locations with Avaya Aura Survivable Remotes. How many components can an Avaya IXTM IP Phone J169 SIP endpoint register to simultaneously?

A. Two Core Session Managers and a Communication Manager Survivable Core

B. Three Core Session Managers and a Branch Session Manager

C. Two Core Session Managers and a Branch Session Manager

D. Five Core Session Managers or Branch Session Managers

Correct Answer: C

QUESTION 5

A customer wants to upgrade their current S8720 Communication Manager 4 (CM) system. They have 2200 users, and a mixture of analog, DCP and IP telephones at their main location. They have six branches with 200-300 stations each served with G700 gateways, each containing an LSP. They want to gain the cost benefits of SIP trunking, and are reluctant to change out the user endpoints, but they want to experiment with a few SIP telephones for some of their remote agents. Survivability and resiliency are essential requirements.

Which elements are required for the solution?

A. Survivable Remote, CM Duplex Core, and Session Border Controller for Enterprise (SBCE)

B. Session Manager (SM), System Manager (SMGR), CM Duplex Core, Survivable Remote with Branch Session Manager, and Session Border Controller for Enterprise (SBCE)

C. Session Manager (SM), System Manager (SMGR), Survivable Remote with Branch Session Manager, and CM Duplex Core

D. Survivable Remote with Branch Session Manager, CM Duplex Core, and Session Border Controller for Enterprise (SBCE)

Correct Answer: A

[Latest 31860X Dumps](#)

[31860X VCE Dumps](#)

[31860X Study Guide](#)