



350-050^{Q&As}

CCIE Wireless Written

Pass Cisco 350-050 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4lead.com/350-050.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

You are tasked with creating a controller-based high-density RF design. Which three factors determine the cell size? (Choose three.)

- A. antenna type
- B. ClientLink support
- C. basic data rate
- D. TPC threshold setting
- E. AP placement
- F. free space path loss

Correct Answer: ACD

QUESTION 2

You are a professional level SQL Sever 2008 Database Administrator in an international corporation named Wiikigo. A 32-bit version is utilized by the instance on a Windows Server 2008 64-bit server. You activate the awe enabled option. A predictable increase in query activity will be experienced by the instance. You are required to figure out the most proper and beneficial time to have the databases migrated to a 64-bit SQL Server 2008 server on the same hardware. A data collector type that proper information is provided should be identified. What kind of collector should you utilize?

- A. You should utilize SQL Trace collector
- B. You should utilize Performance Counters collector
- C. You should utilize T-SQL Query collector
- D. You should utilize Query Activity collector

Correct Answer: B

QUESTION 3

When designing a WLAN network to support both voice and context-aware services, which set of design principles should you follow?

- A. An AP must be placed at the perimeter and in each of the four corners of the floor. All APs must be enabled to ensure proper coverage on the floor to provide -67 dBm, 20 percent cell overlap, and 19 dB channel separation.
- B. An AP must be placed at the perimeter and in each of the four corners of the floor. Some APs may be disabled to ensure proper coverage on the floor to provide -67 dBm, 20 percent cell overlap, and 19 dB channel separation.
- C. An AP must be placed at the perimeter and in each of the four corners of the floor to ensure proper coverage on the



floor to provide -67 dBm, 20 percent cell overlap, and 19 dB channel separation. Some APs may be in monitor mode.

D. If a conflict occurs between the AP placement for voice design and for context-aware location design, then the voice design should take precedence, to protect against delays and dropping of sensitive voice traffic.

E. In a design that includes both voice and context-aware services, voice design always requires more APs to be deployed to ensure -67 dBm coverage, 20 percent cell overlap, 19 dB channel separation, and proper capacity planning.

F. In a design that includes both voice and context-aware services, voice design should take precedence to avoid co-channel interference, which can negatively affect voice quality. Voice design also requires -67 dBm coverage, 20 percent cell overlap, and 19 dB channel separation, which is more difficult to achieve.

Correct Answer: C

QUESTION 4

A network administrator is troubleshooting a problem of a CAPWAP access point that intermittently disconnects from the WLC. The administrator is trying to determine when the problem is happening. UDP port 514 is allowed. What is the best option for successfully gathering comprehensive information about the problem?

A. Configure a script to log into the WLC to gather logs and save them on a PC, where they can be reviewed daily.

B. The CAPWAP AP has no syslog capability but the WLC does have syslog capability. Configure the WLC for syslog and level 1.

C. Configure the CAPWAP AP and the WLC for syslog and level 6.

D. Configure the CAPWAP AP for buffered logging and level 7. Configure the WLC for syslog and level 7.

E. Configure the CAPWAP AP and the WLC for syslog and level 1.

Correct Answer: C

QUESTION 5

In a bridge-to-bridge setup, the network administrator wants to allow only the root bridge the ability to associate to the non-root bridge. To achieve this goal, the administrator decides to implement a MAC filter. If 0017.dfa6.cdf0 is the MAC address of the root AP (ROOT_AP) and 0017.dfa6.ae13 is the MAC address of the non-root AP (NON-ROOT_AP), which command set will achieve this goal?

A. ROOT_AP# configure terminal ROOT_AP(config)# access-list 700 permit 0017.dfa6.cdf0 ROOT_AP(config)# dot11 association mac-list 700

B. NON-ROOT_AP# configure terminal NON-ROOT_AP(config)# access-list 700 permit 0017.dfa6.cdf0 NON-ROOT_AP(config)# dot11 association mac-list 700

C. NON-ROOT_AP# configure terminal NON-ROOT_AP(config)# access-list 700 permit 0017.dfa6.ae13 NON-ROOT_AP(config)# dot11 association mac-list 700

D. NON-ROOT_AP# configure terminal NON-ROOT_AP(config)# access-list 700 permit 0017.dfa6.cdf0 NON-



```
ROOT_AP(config)# dot11 ssid bridge NON-ROOT_AP(config-ssid)# dot11 association mac-list 700
```

```
E. ROOT_AP# configure terminal ROOT_AP(config)# access-list 700 permit 0017.dfa6.cdf0 ROOT_AP(config)#  
interface Dot11Radio0 ROOT_AP(config-if)# dot11 association mac-list 700
```

Correct Answer: B

[350-050 PDF Dumps](#)

[350-050 VCE Dumps](#)

[350-050 Practice Test](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.pass4lead.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 <p>One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <p>Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <p>Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4lead, All Rights Reserved.