

351-001^{Q&As}

CCIE Routing and Switching Written

Pass Cisco 351-001 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass4lead.com/351-001.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



https://www.pass4lead.com/351-001.html

2022 Latest pass4lead 351-001 PDF and VCE dumps Download

QUESTION 1

Which two statements about Layer 2 Frame Prioritization bits are true? (Choose two.)

A. 802.1Q frame headers carry the CoS value in the three most-significant bits of the 2- byte Tag Control Information field.

- B. ISL frame headers carry an IEEE 802.1P CoS value in the three least-significant bits of the 2-byte User field.
- C. ISL frame headers carry an IEEE 802.1P CoS value in the three most-significant bits of the 1-byte User field.
- D. On 802.1Q trunks, traffic in the native VLAN is carried in 802.1Q frames.
- E. Only 802.1Q and ISL frame types can carry CoS information.
- F. On 802.1Q trunks, traffic in the native VLAN is carried in 802.1P frames.

Correct Answer: AE

QUESTION 2

MPLS LDP IGP synchronization is configured on a link. The OSPF adjacency on that link is UP but MPLS LDP synchronization is not achieved. Which statement about this scenario is true?

- A. The router excludes the link from its OSPF LSA type 1.
- B. The router flushes its own router LSA.
- C. The router advertises the link in its router LSA with max-metric.
- D. The router advertises an LSA type 2 for this link, with the metric set to max-metric.
- E. The router advertises the link and OSPF adjacency as it would when the synchronization is achieved.

Correct Answer: C

To enable LDP-IGP Synchronization on each interface that belongs to an OSPF or IS-IS process, enter the mpls Idp sync command. If you do not want some of the interfaces to have LDP-IGP Synchronization enabled, issue the no mpls Idp igp sync command on those interfaces. If the LDP peer is reachable, the IGP waits indefinitely (by default) for synchronization to be achieved. To limit the length of time the IGP session must wait, enter the mpls Idp igp sync holddown command. If the LDP peer is not reachable, the IGP establishes the adjacency to enable the LDP session to be established. When an IGP adjacency is established on a link but LDP-IGP Synchronization is not yet achieved or is lost, the IGP advertises the max-metric on that link.

Reference: http://www.cisco.com/c/en/us/td/docs/ios/12_0s/feature/guide/fsldpsyn.html

QUESTION 3

Which two options are the two main phases of PPPoE? (Choose two.)

A. Active Discovery Phase

https://www.pass4lead.com/351-001.html

2022 Latest pass4lead 351-001 PDF and VCE dumps Download

- B. IKE Phase
- C. Main Mode Phase
- D. PPP Session Phase
- E. Aggressive Mode Phase
- F. Negotiation Phase

Correct Answer: AD

PPPoE is composed of two main phases:

Active Discovery Phase -- In this phase, the PPPoE client locates a PPPoE server, called an access concentrator. During this phase, a Session ID is assigned and the PPPoE layer is established.

PPP Session Phase -- In this phase, PPP options are negotiated and authentication is performed. Once the link setup is completed, PPPoE functions as a Layer 2 encapsulation method, allowing data to be transferred over the PPP link within

PPPoE headers.

Reference: http://www.cisco.com/c/en/us/td/docs/security/asa/asa92/configuration/vpn/asa- vpn-cli/vpn-pppoe.html

QUESTION 4

Refer to the exhibit.

Switch# Vlan	show ip igmp snooping mrouter ports
10	Gi2/0/1(dynamic), Router
20	Gi2/0/1 (dynamic), Router

Which three statements about the output are true? (Choose three.)

- A. An mrouter port can be learned by receiving a PIM hello packet from a multicast router.
- B. This switch is configured as a multicast router.
- C. Gi2/0/1 is a trunk link that connects to a multicast router.
- D. An mrouter port is learned when a multicast data stream is received on that port from a multicast router.
- E. This switch is not configured as a multicast router. It is configured only for IGMP snooping.
- F. IGMP reports are received only on Gi2/0/1 and are never transmitted out Gi2/0/1 for VLANs 10 and 20.

Correct Answer: ABC

In this example, the switch has been configured as a multicast router since IGMP snooping has been enabled. All



https://www.pass4lead.com/351-001.html 2022 Latest pass4lead 351-001 PDF and VCE dumps Download

mrouters can learn about other mrouters by receiving a PIM hello packet from another multicast router. Also, since two different VLANs are being used by the same port of gi 2/0/1, it must be a trunk link that connects to another multicast router.

QUESTION 5

Which option is the default point of insertion for the BGP cost community?

- A. before best path calculation
- B. after best path calculation
- C. after the IGP metric comparison
- D. after the router ID comparison

Correct Answer: C

Latest 351-001 Dumps

351-001 PDF Dumps

351-001 Braindumps



To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.pass4lead.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4lead, All Rights Reserved.