

4A0-100^{Q&As}

Alcatel-Lucent Scalable IP Networks

Pass Alcatel-Lucent 4A0-100 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/4a0-100.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Alcatel-Lucent Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

What capability of TCP/IP allows two hosts to have multiple TCP sessions to each other simultaneously?

- A. The combination of IP source and destination address and TCP source and destination port uniquely identifies each session.
- B. The combination of IP source and destination address and the IP protocol field uniquely identifies each session.
- C. The hosts can identify the sessions using each others MAC addresses.
- D. Two hosts can not have multiple TCP sessions simultaneously.

Correct Answer: A

QUESTION 2

On what type of device/router is a Service Access Point (SAP) defined?

- A. The SAP is defined on the CE device.
- B. The SAP is defined on the PE device.
- C. The SAP is defined on the P device.
- D. The SAP is defined on both CE and PE devices.

Correct Answer: B

QUESTION 3

What must occur before a LAG becomes operational?

- A. There must be multiple ports assigned to the LAG.
- B. All ports in the LAG must be configured with the same speed and duplex settings.
- C. Auto-negotiation must be enabled on all ports in the LAG.
- D. The duplex setting on all the ports must be forced to half.
- E. Auto-negotiation must be set to limited or disabled on at least one member port.

Correct Answer: B

QUESTION 4

Which of the following statements is TRUE of Layer 3 addressing?

- A. Internet devices on the same network can have the same Layer 3 address in different broadcast domains.
- B. Every Host device must have a unique Layer 3 address in order to access the Internet.
- C. Internet devices need unique Layer 3 addresses to communicate directly with upper layers.
- D. A router must have only one address to allow it to be uniquely identified.

Correct Answer: B

QUESTION 5

Which of the following is NOT a valid log source in a Nokia 7750 SR?

- A. Main
- B. Security
- C. Syslog
- D. Debug

Correct Answer: C

[4A0-100 VCE Dumps](#)

[4A0-100 Exam Questions](#)

[4A0-100 Braindumps](#)