

# 4A0-C01<sup>Q&As</sup>

Nokia NRS II Composite Exam

## Pass Nokia 4A0-C01 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/4a0-c01.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



#### QUESTION 1

What modes of authentication are supported for RIPv2 on the Alcatel-Lucent 7750 SR?

- A. RIPv2 supports basic and MD5 authentication only.
- B. RIPv2 supports password and MD5 authentication only.
- C. RIPv2 does not support authentication, password and MD5 authentication.
- D. RIPv2 does not support authentication.

Correct Answer: C

---

#### QUESTION 2

What happens by default on an Alcatel-Lucent 7750 SR when a VPLS accepts a tagged frame at the ingress SAP 1/1/1:100?

- A. The FCS is verified and kept in the customer frame. The VLAN tag is kept and transported over the network.
- B. The FCS is verified and kept in the customer frame. The VLAN tag is removed for transport over the network.
- C. The FCS is verified and removed from the frame. The VLAN tag is kept for transport over the network.
- D. The FCS is verified and removed from the frame. The VLAN tag is removed for transport over the network.

Correct Answer: D

---

#### QUESTION 3

Facility fast reroute with node protection is enabled for an LSP, which of the following is FALSE?

- A. Each PLR signals a bypass tunnel that avoids the next-hop downstream router.
- B. When a failure occurs, the PLR pushes an additional label onto the label stack.
- C. No bypass tunnel is established if the PLR cannot provide node protection.
- D. The head-end router sets the local protection desired flag in the session attribute object.

Correct Answer: C

---

#### QUESTION 4

What are the ways the RID can be created on an Alcatel-Lucent 7750 SR router? (Choose three) A. From the last 32 bits of the chassis MAC address

- B. From the first 32 bits of the chassis MAC address

- C. The loopback IP address
- D. By using the command "config router ospf rid X.X.X.X"
- E. From the system IP address
- F. From the highest interface IP address

Correct Answer: ADE

---

#### QUESTION 5

An SDP using GRE encapsulation is configured for an E-pipe service. The network port used by the SDP has an MTU of 8000. What value does the SDP path MTU have by default on an Alcatel-Lucent 7750 SR?

- A. 7958
- B. 7978
- C. 8022
- D. 8042

Correct Answer: A

[4A0-C01 Practice Test](#)

[4A0-C01 Exam Questions](#)

[4A0-C01 Braindumps](#)