

5V0-42.21^{Q&As}

VMware SD-WAN Design and Deploy Skills

Pass VMware 5V0-42.21 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/5v0-42-21.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

What are three key benefits of VMware SD-WAN? (Choose three)

- A. Provision Edges in minutes
- B. Automated configuration of cloud resources
- C. Remove requirement of Edge devices
- D. Gain visibility across any link
- E. Layer 2 VPNs between sites
- F. Reduce the burden on MPLS

Correct Answer: BCF

QUESTION 2

Which statement is correct about VMware SD-WAN Orchestrator user roles and their associate privileges?

- A. Customer Support User can view and manage then company\\'s network
- B. Standard Admin User can view but cannot manage their customer.
- C. Superuser: User can view but cannot create additional admin.
- D. Enterprise read only: User can view but not modify configurations.

Correct Answer: A

QUESTION 3

A network architect is designing a VMware SD-WAN architect for customer using VMware hosted VCO and VCGs, white VCEs will be deployed at the customer\\'s branches and data centers. The network architect would like to achieve control plane redundancy. Which action, if any, should be taken to meet this goal?

- A. Multiple VCGs are automatically assigned to every VCE and control plane on VCU is always enabled, so control plane redundancy has been taken care of already
- B. Multiple VCFs at data centers can be contoured to function as route reflectors to achieve control plane redundancy.
- C. VCGs automatically assigned to a VCF. do not participate in control plane At least two dedicated Controllers should be manually assigned for each VCGs to achieve control plane redundancy.
- D. VCGs automatically assigned to a VCE do not participate in control plane At least two dedicated Controllers should be manually assigned for the customer to achieve control plane redundancy

Correct Answer: B

QUESTION 4

A customer is looking to have Quality of Service (QoS), resource allocations, link/path steering, and error correction applied automatically based on applications. Which component of VMware SD-WAN helps the customer achieve this requirement?

- A. Overlay Flow Control
- B. High Availability Configuration
- C. Business Policy Framework
- D. Branch Site Topologies

Correct Answer: C

QUESTION 5

Given a VMware SD WAN Branch Edge with Dual Internet links A and B:

Link A has 50 Mb capacity and latency 10ms

Link H has 50 Mb capacity and latency 10ms

A database backup of 40Mbps is parted, and the traffic classified as low priority bulk traffic.

Which statement is correct?

- A. DMPO will perform pen How load balancing.
- B. Packet duplication will take plant? to ensure both links are optimized.
- C. Packets will be sent nut the highest latency link first as this is low priority bulk traffic
- D. Link Aggregation may take place, and both links could be used.

Correct Answer: D

[Latest 5V0-42.21 Dumps](#)

[5V0-42.21 Study Guide](#)

[5V0-42.21 Braindumps](#)