

# 600-210<sup>Q&As</sup>

Implementing Cisco Service Provider Mobility UMTS Networks

## Pass Cisco 600-210 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/600-210.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



### QUESTION 1

In MGT-based routing, which option is the GT address format of the called party?

- A. E.212
- B. E.164
- C. E.412
- D. E.214
- E. E.216

Correct Answer: D

### QUESTION 2

Your company wants to limit bandwidth for Skype traffic. You have been tasked to configure Application Detection and Control using the Cisco ASR 5000 to detect Skype traffic for all subscribers. If Skype traffic is detected, limit the uplink and downlink data rate to 32 kb/s. Which required configuration is needed to complete this task?

- A. active-charging service ACS\_ACME p2p-detection protocol skype

```
ruledef skype_detection
```

```
p2p protocol = skype
```

```
exit
```

```
charging-action skype_rate_limit
```

```
content-id 1500
```

```
flow limit-for-bandwidth direction downlink peak-data-rate 32000 peak-burst- 8000 violate- action
```

```
discard
```

```
flow limit-for-bandwidth direction uplink peak-data-rate 32000 peak-burst- 8000 violate- action discard
```

```
rulebase acme_rulebase
```

```
action priority 1000 ruledef skype_detection charging-action skype_rate_limit
```

- B. active-charging service ACS\_ACME ruledef skype\_detection p2p protocol = skype exit charging-action skype\_rate\_limit content-id 1500 flow limit-for-bandwidth direction downlink peak-data-rate 16000 peak-burst- 8000 violate- action discard flow limit-for-bandwidth direction uplink peak-data-rate 16000 peak-burst- 8000 violate- action discard rulebase acme\_rulebase action priority 32000 ruledef skype\_detection charging-action skype\_rate\_limit

- C. active-charging service ACS\_ACME p2p-detection protocol skype ruledef skype\_detection p2p protocol = skype flow limit-for-bandwidth direction downlink peak-data-rate 32000 peak-burst- 8000 violate- action discard flow limit-for-

bandwidth direction uplink peak-data-rate 32000 peak-burst- 8000 violate- action discard exit rulebase acme\_rulebase action priority 1000 ruledef skype\_detection

D. active-charging service ACS\_ACME p2p-detection protocol skype ruledef skype\_detection p2p protocol = skype\_traffic exit charging-action skype\_rate\_limit content-id 1500 flow limit-for-credit direction downlink peak-data-rate 32000 peak-burst- 8000 violate- action discard flow limit-for-credit direction uplink peak-data-rate 32000 peak-burst- 8000 violate-action discard rulebase acme\_rulebase action priority 1000 ruledef skype\_detection charging-action skype\_rate\_limit

Correct Answer: A

---

### QUESTION 3

Your company has decided to implement URL blacklisting for the ACME company rulebase and discard any blacklisted matches found in subscriber HTTP traffic. Which configuration accomplishes this task?

A. active-charging service acme\_acs url-blacklisting method exact-match rulebase acme\_rulebase urlblacklisting action discard

B. active-charging service acme\_acs url-blacklisting method exact-match rulebase acme\_rulebase urlblacklisting action terminate-flow

C. active-charging service acme\_acs url-blacklisting method http post url-blacklisting method http get rulebase acme\_rulebase url-blacklisting action discard

D. active-charging service acme\_acs url-blacklisting method http post url-blacklisting method http get rulebase acme\_rulebase url-blacklisting action terminate-flow

Correct Answer: A

---

### QUESTION 4

For inbound Inter-System RAU, which message sends the SGW change indication to the old SGSN?

A. context request

B. context response

C. context acknowledgment

D. modify bearer request

E. modify bearer response

Correct Answer: C

---

**QUESTION 5**

Which part of the OSI model contains the Signalling Connection Control Part protocol?

- A. Data link layer
- B. Network layer
- C. Transport layer
- D. Application layer
- E. Presentation layer

Correct Answer: B

[Latest 600-210 Dumps](#)

[600-210 PDF Dumps](#)

[600-210 Practice Test](#)