

701-100^{Q&As}

DevOps Tools Engineer Exam

Pass Lpi 701-100 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/701-100.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Lpi Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which of the following tasks can Logstash fulfill without using other components of the Elastic Stack? (Choose three.)

- A. Receive log data from remote systems.
- B. Store log data persistently.
- C. Aggregate log data over a period of time.
- D. Process log data to extract information.
- E. Forward log data to other services.

Correct Answer: ADE

QUESTION 2

Which property of a Kubernetes Deployment specifies the number of instances to create for a specific Pod? (Specify ONLY the option name, no matter of its location in the object hierarchy)

- A. The property you are looking for is replicas. This is a field directly under the Deployment object and specifies the number of Pod replicas that should be maintained by the Deployment.

Correct Answer: A

QUESTION 3

What is the purpose of cloud-init?

- A. Assign an IaaS instance to a specific computing node within a cloud.
- B. Standardize the configuration of infrastructure services, such as load balancers or virtual firewalls in a cloud.
- C. Prepare the generic image of an IaaS instance to fit a specific instance's configuration.
- D. Replace common Linux init systems, such as systemd or SysV init.
- E. Orchestrate the creation and start of multiple related IaaS instances.

Correct Answer: C

QUESTION 4

When creating a new Docker network, which mechanisms are available for address assignments to containers on the new network? (Choose TWO correct answers.)

- A. By default, Docker chooses an unused private address space and assigns addresses from this network to containers.
- B. All networked containers must contain at least one IPADDRESS statement in their Dockerfile specifying the container's address.
- C. Docker does not configure IP addresses and relies on the containers to configure their network interface with a valid IP address.
- D. By default, Docker requests one address per container using DHCP on the interface used by the host system's default route.
- E. Docker network create allows specifying a network to be used for container addressing using --subnet.

Correct Answer: AD

QUESTION 5

Which docker subcommand starts a new container? (Specify only the subcommand without any path or parameters.)

- A. run

Correct Answer: A

[701-100 Practice Test](#)

[701-100 Study Guide](#)

[701-100 Exam Questions](#)