

71800X^{Q&As}

71800X - Avaya IX Messaging Implementation and Maintenance

Pass Avaya 71800X Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/71800x.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

In the event of one or more VSN failures in a High Availability architecture, which component provides continuous voice messaging and message retrieval to all registered users?

- A. Voice Server Node
- B. Content Sync Engine
- C. Carbonite server
- D. Consolidated Server

Correct Answer: A

QUESTION 2

Which three statements about the recommended hardware requirements of Avaya IX

- A. Configure the CPU for Performance mode in the server's BIOS settings.
- B. All processors are to be Intel?2.0 GHz or better.
- C. Different configurations must be used for both physical and virtual servers.
- D. All processors are to be Intel?3.5 GHz or better.
- E. All hard drives must be high performance, server grade drives.

Correct Answer: ACD

QUESTION 3

If SR140 fax port licenses are present, how many FAX channels are supported by Avaya IX,M Messaging?

- A. 48 ports per voice server, 120 max/solution
- B. 24 ports per voice server, 120 max/solution
- C. 24 ports per voice server, 60 max/solution
- D. 48 ports per voice server, 60 max/solution

Correct Answer: D

QUESTION 4

In Avaya IXTM Messaging High Availability, VSN is designed to support up to how many SIP ports?

- A. 100
- B. 120
- C. 150
- D. 220

Correct Answer: A

QUESTION 5

Which three requirements must be met for an Avaya IXTM Messaging High Availability installation? (Choose three.)

- A. Maximum round-trip latency between the voice servers and the PBX must not exceed 200 milliseconds. Optimal round-trip latency is less than 150 milliseconds.
- B. All servers must be part of the same Windows domain.
- C. All servers must have a minimum 1 Gb/s connection to the network.
- D. Maximum round-trip latency between the voice servers and the consolidated servers must not be more than 50 milliseconds.
- E. The path of connectivity must have 2 Mb/s guaranteed bandwidth with no steady-state congestion.

Correct Answer: BCE

[71800X PDF Dumps](#)

[71800X VCE Dumps](#)

[71800X Practice Test](#)