

E20-329^{Q&As}

Technology Architect Backup and Recovery Solutions Design Exam

Pass EMC E20-329 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/e20-329.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

An EMC NetWorker customer is considering backup options for their VMware environment. The environment consists of Microsoft Windows file servers and an Oracle database server running on Solaris. What is an advantage of using the VMware image backup operation?

- A. Application backup data is crash-consistent
- B. File-level restore granularity available for all systems
- C. Low load on the ESX server during backups
- D. No proxy server required for the backup environment

Correct Answer: A

QUESTION 2

An EMC NetWorker customer has three backup servers with four storage nodes reporting to each of the backup servers. All servers run Microsoft Windows. A dual-engine EMC Disk Library with Active Engine Failover is being proposed for this environment with embedded storage nodes for to physical tape. What is a consideration for this solution?

- A. Active Engine Failover is unsupported in a Windows environment
- B. Multiple instances of the embedded storage node will need to be configured
- C. Each embedded storage node can only serve a single data zone
- D. NetWorker servers must be configured as read storage nodes for the cloning operation

Correct Answer: B

QUESTION 3

A customer has recently purchased Data Protection Advisor (DPA) to monitor their EMC NetWorker backup environment. They are currently monitoring the NetWorker servers and storage nodes. Which other devices can be monitored without additional DPA licenses?

- A. Physical or virtual tape libraries, IP and Fibre Channel switches, and databases on backup clients
- B. NAS devices and performance data on backup clients
- C. IP switches, Fibre Channel switches, tape libraries, and NAS devices
- D. Physical or virtual tape libraries and IP or Fibre Channel switches only

Correct Answer: A

QUESTION 4

Refer to Scenario

EMC NetWorker, using a VADP proxy, is backing up 12 virtual machines concurrently. What is the total recommended additional RAM needed on the proxy?

- A. 6 GB
- B. 8 GB
- C. 10 GB
- D. 12 GB

Correct Answer: A

QUESTION 5

An EMC Avamar customer's Gen-1 system with 4 TB of GSAN capacity has reached read-only threshold. The customer indicates that the deduplicated backup data accounts for approximately 3.5 TB.

What is the most likely cause for the read-only threshold being reached?

- A. Deduplication rate is less than expected, accounting for the remaining GSAN capacity
- B. Combination of system overhead, logs, and checkpoints account for the remaining GSAN capacity
- C. RAIN overhead accounts for the remaining available GSAN capacity
- D. Checkpoints and logs account for the remaining GSAN capacity

Correct Answer: C

[E20-329 Practice Test](#)

[E20-329 Study Guide](#)

[E20-329 Exam Questions](#)