

E20-351^{Q&As}

Storage Attached Network (SAN) Speacilalist Exam

Pass EMC E20-351 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass2lead.com/e20-351.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



https://www.pass2lead.com/e20-351.html

QUESTION 1

EMC Customer Service has determined a customers DS4100B needs to be replaced. After bringing the replacement switch (another DS4100B) online, the storage administrator recognizes the Microsoft Exchange MSCS cluster cannot access the CX 3-80 storage over one (1) of its two (2) 4 Gb/s HBA paths. What is the likely problem?

- A. Customer Service engineer configured the wrong IP address for the replacementDS4100B, hence creating an IP conflict with the other fabrics good DS4100B
- B. Customer Service engineer didnt move the old GBICs to the new switch, hence theswitchport GBIC now has a different WWN.
- C. The customer has standardized on hard zoning, and the Customer Service engineerplugged one of the CX 3-80 storage ports into the wrong DS4100B switch port.
- D. The customer has standardized on soft zoning, and the Customer Service engineerplugged one of the CX 3-80 storage ports into the wrong DS4100B switch port.

Correct Answer: C

QUESTION 2

When enabling zoning security on a Connectrix B-Series switch, on which switch in the SAN can zoning be performed?

- A. A remote server with LDAP security
- B. Any switch in the fabric
- C. Only the primary Fibre Channel switch
- D. The primary and secondary Fabric Channel switches

Correct Answer: C

QUESTION 3

A customer has an existing SAN that is being managed by Control Center. Five new Linux hosts have been deployed to the SAN. Which step must be taken in order to discover the new Linux hosts?

- A. Once a master agent has been installed on the hosts, the hosts will be automatically discovered.
- B. Provide the host\\'s IP address in the Control Center Console, and choose discover.
- C. The Control Center server must be restarted to discover the new hosts.
- D. The hosts must be restarted and the Control Center server will discover them.

Correct Answer: A



https://www.pass2lead.com/e20-351.html

2024 Latest pass2lead E20-351 PDF and VCE dumps Download

QUESTION 4

The AP-7420B switch, which uses XPath OS, has many features that may not be supported in particular environments. Besides the EMC Support Matrix, what is the other recommended reference for up-to-date, last-minute support and implementation information?

- A. CLARiiON Open Systems Configuration Guide
- B. Connectrix B-Series Student Resource Guide
- C. EMC Networked Storage Topology Guide
- D. SWAT (Switch Analysis Tool)

Correct Answer: C

QUESTION 5

Which type of Fibre Channel ports are used when creating an ISL?

- A. E_Port
- B. F_Port
- C. N_Port
- D. NL_Port

Correct Answer: A

E20-351 PDF Dumps

E20-351 Study Guide

E20-351 Braindumps