

E20-517^{Q&As}

Symmetrix Solutions Specialist Exam for Storage Administrators

Pass EMC E20-517 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/e20-517.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A customer is implementing EMC VMAX and wants to manage it using Unisphere for VMAX.

Which entitlement must the VMAX system contain to achieve this goal?

- A. Unisphere for VMAX (SMC) eLicense
- B. Unisphere for VMAX Capacity-Based License
- C. Unisphere for VMAX Open Storage eLicense
- D. Unisphere for VMAX Host-Based License

Correct Answer: A

QUESTION 2

A storage administrator would like to alter the polling interval of the event daemon that is monitoring thin pools in a Symmetrix.

How can this be accomplished?

- A. Make changes to the daemon options file (/var/symapi/config/daemon_options) and reload the options (stordaeomon action storevntd -cmd reload)
- B. Make changes to the options file (/var/symapi/config/options) and reload the options (stordaeomon action storevntd -cmd reload)
- C. Make changes to the daemon users file (/var/symapi/config/daemon_users) and restart the event daemon
- D. Make changes to the README.daemon options file (/var/symapi/config/README.daemon_options) restart the event daemon

Correct Answer: A

QUESTION 3

What is the state of the standard and BCV devices after a full TimeFinder/Mirror "Establish" has been initiated?

- A. Standard is Read Only and BCV is Not Ready
- B. Standard is Read Only and BCV is Read Only
- C. Standard is Read/Write and BCV is Not Ready
- D. Standard is Read/Write and BCV is Read/Write

Correct Answer: A

QUESTION 4

After acquiring a company 300 hundred miles from their current office, a customer has asked EMC to help to design a single-hop application recovery plan. After careful analysis of the workload and available bandwidth, SRDF/AR was selected as the solution.

If the SRDF/AR cycle time is set to 90 minutes, what is the maximum potential data loss?

- A. 1.5 hours of data
- B. 2 hours of data
- C. 3 hours of data
- D. 4.5 hours of data

Correct Answer: C

QUESTION 5

TimeFinder/Snap virtual devices (VDEVs) will be used as the control devices in an Open Replicator implementation.

Which Open Replicator copy operation is supported?

- A. Cold Push
- B. Cold Pull
- C. Hot Push
- D. Hot Pull

Correct Answer: A

[Latest E20-517 Dumps](#)

[E20-517 PDF Dumps](#)

[E20-517 VCE Dumps](#)