



HP0-Y46^{Q&As}

Implementing HP Network Technologies

Pass HP HP0-Y46 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4lead.com/HP0-Y46.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Refer to the HP Provision and HP Comware configurations.

```
#ProVision
vlan 1 untagged A1
vlan 2 tagged A2
trunk A1-A2 trk1 lacp

#Comware
vlan 1
vlan 2
interface bridge-aggregation 1
  link-aggregation mode dynamic
quit
interface g1/0/1
  port link-aggregation group 1
  port link-type trunk
  port trunk pvid vlan 1
  port trunk permit vlan 2
quit
interface g1/0/2
  port link-aggregation group 1
  port link-type trunk
  port trunk pvid vlan 1
  port trunk permit vlan 2
quit
```

An aggregated link has been defined between the Provision A1 and A2 switches, as well as between the Comware g1/0/1 and g1/0/2 switches. 1 and 2 is not being passed between the switches. However, during the network administrator's tests, traffic for VLAN. What is the cause of this problem?

- A. The PVID on the Comware switch does not match the Provision switch
- B. The VLAN properties need to be defined on A1 and A2 of the Provision switch.
- C. The aggregated link protocol does not match on the two switches
- D. The VLAN properties need to be defined on BAGG1 of the Comware switch

Correct Answer: A



QUESTION 2

Which URLs can a network administrator use to access IMC? (Select two.)

- A. http://:8080/imc
- B. http://:8000
- C. http://:8043
- D. http://:8443/imc
- E. http://

Correct Answer: AC

QUESTION 3

Refer to the partial command output.

```
<Comware> display link-aggregation verbose bridge-aggregation 2
<-output omitted->
Aggregation Interface: Bridge-Aggregation2   Aggregation Mode: Dynamic
Loadsharing Type: Shar
System ID: 0x8000, 000f-e267-6c6a
Local:
  Port      Status  Priority  Oper-Key  Flag
-----
GE1/0/3    S       32768    2         {AG}
GE1/0/4    S       32768    2         {AG}
Remote:
  Actor     Partner  Priority  Oper-Key  SystemID      Flag
-----
GE1/0/3    32       32768    2         0x8000, 000f-e267-57ad {AG}
GE1/0/4    26       32768    2         0x8000, 000f-e267-57ad {AG}
```

Based on this output, which statement is true?

- A. Static LACP is used, and load sharing is functioning.
- B. Dynamic LACP is used, and load sharing has failed.
- C. Static LACP is used, and load sharing has failed.
- D. Dynamic LACP is used, and load sharing is functioning.

Correct Answer: D

QUESTION 4



A network administrator has installed IMC and the appropriate licenses. The network administrator is attempting to import the HP Comware and HP Provision switches into IMC but are experiencing problems importing the Comware switches. The network administrator verifies the SNMFV2c configuration on both sets of switches and the SNMP configuration in IMC. The SNMP parameters are correct.

What is the cause of the import problem?

- A. Comware switches implement SNMFV3 by default.
- B. Comware switches do not have telnet fully configured
- C. Comware switches are not fully supported by IMC.
- D. Comware switches require SSH to be configured for remote CLI access.

Correct Answer: D

QUESTION 5

A network administrator executes the following command:

```
[Comware-1] display brief interface
The brief information of interface(s) under route mode:
Interface          Link      Protocol-link  Protocol type  Main IP
NULL0              UP        UP(spoofing)  NULL           --
Vlan1              DOWN     DOWN          ETHERNET       10.1.1.1
Vlan2              UP        UP            ETHERNET       10.2.2.1
<-output omitted->
```

What is the state of the VLAN 1 interface?

- A. All interfaces in VLAN 1 are down.
- B. The IP address of VLAN 1 conflicts with another device in VLAN 1.
- C. The IP address for VLAN 1 is a duplicate of another VLAN interface on the switch.
- D. VLAN 1 has a single port in a down state.

Correct Answer: D

[HP0-Y46 Study Guide](#)

[HP0-Y46 Exam Questions](#)

[HP0-Y46 Braindumps](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.pass4lead.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 <p>One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <p>Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <p>Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4lead, All Rights Reserved.