ACMP_6.4^{Q&As}

Aruba Certified Mobility Professional 6.4

Pass Aruba ACMP_6.4 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass2lead.com/acmp_6-4.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Aruba Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

What is the blacklist default time?

A. 30seconds

B. 1800 seconds

C. 3600 seconds

D. No default time, it must be done manually

E. 1 day

Correct Answer: C

QUESTION 2

AAA Profile > employee1-aaa_prof   [Show Reference] [Save As] [Reset]

Initial role	logon
MAC Authentication Default Role	guest
802.1X Authentication Default Role	employee
Download Role from CPPM	☐
L2 Authentication Fail Through	☐
Multiple Server Accounting	☐
User idle timeout	☐ Enable seconds
RADIUS Interim Accounting	☐
User derivation rules	scanner
Wired to Wireless Roaming	☑
SIP authentication role	--NONE--
Device Type Classification	☑
Enforce DHCP	☐
PAN Firewall Integration	☐

802.1X Authentication Profile > dot1x_prof-bsi53   [Show Reference] [Save As] [Reset]

Basic | Advanced

Max authentication failures	0	
Enforce Machine Authentication	☑	
Machine Authentication: Default Machine Role	denyall	
Machine Authentication: Default User Role	guest	
Reauthentication	☐	
Termination	☐	
Termination EAP-Type	☐ eap-tls	☐ eap-peap
Termination Inner EAP-Type	☐ eap-mschapv2	☐ eap-gtc

The screen captures above show the 802.1X authentication profile and AAA profile settings for a VAP.
Ifmachineauthenticationpassesanduserauthenticationfails, whichrolewillbeassigned?

A. employee

B. denyall

C. guest

D. logon

E. no role is assigned

Correct Answer: B

![Pass2Lead](https://Pass2Lead.com)
QUESTION 3

The Aruba Policy Enforcement Firewall (PEF-NG) module supports destination network address translation (dst-nat). Which is the default use of this statement in an Aruba controller configuration?

A. source the IP addresses of users to specific IP address

B. redirectHTTPsessionstoCaptivePortal

C. redirect Access Points to another Aruba controller

D. provide a telnet connection to the controller

E. redirect a SSH session to terminate on the controller

Correct Answer: B

QUESTION 4

How does the ARM Band Steering feature encourage 5GHz capable clients to move/connect to the 5GHz radios of Aruba APs?

A. ARM suppresses the probe responses on the 2.4 ghz radio?

B. ARM utilizes third party software on the wireless clients

C. Current Wi-Fi chipset firmware supports this by default

D. It\\'s not possible the move clients to 5GHz radios when they can see both 2.4 and 5GHz APs

E. ARM disables the 2.4Ghz radio for the specified client

Correct Answer: A

QUESTION 5

Which profiles are required in an AP Group to enable an SSID with VLAN 1, WPA2 and LMSIP?(Choose three)

A. Virtual-AP profile

B. WLAN profile

C. 802.1x authentication profile

D. AP System Profile

E. SSID Profile

Correct Answer: ADE

ACMP_6.4 VCE Dumps   ACMP_6.4 Practice Test   ACMP_6.4 Braindumps