

C2150-609^{Q&As}

IBM Security Access Manager V9.0 Deployment

Pass IBM C2150-609 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/c2150-609.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

An IBM Security Access Manager V9.0 deployment at a customer has enabled audit.authz, audit.authn, audit.http for meeting auditing requirements and results in large volume of audit records and poses significant data management challenges to the client. The customer wants to exclude the audit events to certain static resources such as images.

What action should be taken to implement this?

- A. Disable audit.http events only
- B. Disable audit.http.unsuccessful events only
- C. Define a POP with the audithttp set to "no"; attach this to the static resources
- D. Define an ACL with the audithttp operation set to "no"; attach this to the static resources

Correct Answer: D

QUESTION 2

Which two resources should a deployment professional check to ensure an appliance is at the very latest level? (Choose two.)

- A. IBM Fix Central
- B. IBM Security YouTube channel
- C. Google IBM Security Access Manager V9.0 Circle
- D. LinkedIn IBM Security Access Manager V9.0 Group
- E. Fixes by version for IBM Security Access Manager V9.0

Correct Answer: AE

QUESTION 3

A customer has setup IBM Security Access Manager V9.0 hardware appliances (AP, A1, A2) in a cluster. The appliances (A1, A2) that host reverse proxies are labeled as "restricted" in the cluster. AP is the Primary of the cluster.

There is one reverse proxy in appliance A1 and two in appliance A2. These reverse proxies are being tuned for performance. The appliance A1 and A2 max socket range has been set to 64510. What is true in this situation?

- A. The appliance AP cannot be used for running reverse proxies to balance load
- B. The reverse proxy in appliance A1 can have a maximum thread count of 30,000
- C. Both reverse proxies in appliance A2 can have a maximum thread count of 30,000
- D. Appliance A2 with two reverse proxies will perform better than Appliance A1 with one reverse proxy

Correct Answer: C

QUESTION 4

There is an SSL connectivity issue between the IBM Security Access Manager V9.0 Reverse Proxy and the backend business application.

Which Two troubleshooting commands under Tools in the application SSH interface can be used to validate the Reverse Proxy can successfully connect to the backend host: secure-port? (Choose two.)

- A. Ping
- B. Session
- C. Connect
- D. Traceout
- E. Connections

Correct Answer: BC

Reference: https://www.ibm.com/support/knowledgecenter/SSPREK_9.0.2/com.ibm.isam.doc/admin/concept/con_appliance_cli.html

QUESTION 5

During installation WebSEAL provides a default certificate key database that is used to authenticate both clients and junctioned servers.

Which stanza entry of the WebSEAL configuration file points to the default certificate key database (i.e. kdb file)?

- A. ssl-keyfile
- B. jct-cert-keyfile
- C. webseal-cert-keyfile
- D. webseal-cert-keyfile-label

Correct Answer: C

[Latest C2150-609 Dumps](#)

[C2150-609 VCE Dumps](#)

[C2150-609 Braindumps](#)