DES-4421^{Q&As}

Specialist - Implementation Engineer, PowerEdge MX Modular Exam

Pass EMC DES-4421 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass2lead.com/des-4421.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

What is the number of server-facing ports and the bandwidth of each port on the MXG610s? (Choose two.)

A. 8x 16 Gbps

B. 16x 32 Gbps

C. 16x 16 Gbps

D. 8x 32 Gbps

Correct Answer: BC

Reference: https://i.dell.com/sites/csdocuments/Product_Docs/en/DellEMCNetworkingMXG610sSpecSheet.pdf (page 1)

QUESTION 2

What is the maximum possible weight of a fully populated MX7000 chassis?

A. 250 lbs (114 kg)

B. 300 lbs (136 kg)

C. 400 lbs (182 kg)

D. 500 lbs (227 kg)

Correct Answer: C

Reference: https://www.dell.com/support/manuals/us/en/04/poweredge-mx7000/pemx7000_ts_pub/chassis-weight?guid=guid-41294709-f48d-4174-846d-2fefc1483aefandlang=en-us

QUESTION 3

What is a valid option when resetting iDRAC to factory defaults?

A. Preserve user and network settings

B. Preserve network and storage settings

C. Preserve identity and network settings

D. Preserve storage and user settings

Correct Answer: A

Reference: https://www.dell.com/support/manuals/us/en/04/poweredge-r740/idrac_3.21.21.21_ug/reset-idrac-and-reset-idrac-to-default?guid=guid-1b5c2d57-05c8-4098-8344-49c984839c30andlang=en-us

QUESTION 4

An administrator is connecting two MX840c to an MX5016s. The MX5016s is configured in Enclosure Assigned mode. What should the requirements of this mode be to avoid configuration issues?

A. MX745P with a cluster aware OS

B. MX745P with no OS restrictions

C. HBA330MMZ with no OS restrictions

D. HBA330MMZ with a cluster aware OS

Correct Answer: A

Reference: https://i.dell.com/sites/csdocuments/Product_Docs/en/poweredge-mx5016s-mx5000s-technical-guide.pdf (p.10)

QUESTION 5

An administrator is asked to install and power-on a new MX740c sled in an MX7000 chassis. The administrator inserts the sled and presses the power button. They notice that the power button LED is blinking green. After a short time power button turns to solid green and the server finally turns on.

What operation was in progress when the power button was blinking green?

A. iDRAC was booting

B. Lifecycle Controller update was in progress

C. Lifecycle Controller was taking firmware inventory

D. iDRAC was updating firmware

Correct Answer: A

[Latest DES-4421 Dumps](#)   [DES-4421 VCE Dumps](#)   [DES-4421 Braindumps](#)