

# DES-4421<sup>Q&As</sup>

Specialist - Implementation Engineer, PowerEdge MX Modular Exam

**Pass EMC DES-4421 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/des-4421.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

What is a characteristic of MX7000 networking in Full Switch Mode?

- A. Layer 2 bridging is disabled by default and interfaces must join a bridge domain (VLAN) before being able to forward frames.
- B. Networking is enabled by default and all switch-specific OS10EE capabilities are available.
- C. Networking is available on MX9116n FSE and MX7116n FEM but not on the MX5108n.
- D. Switches operate as layer 2 I/O aggregation devices and are managed through OME-M.

Correct Answer: B

Reference: <https://infohub.delltechnologies.com/l/test2-poweredge-mx-networking-architecture-guide-1/operating-modes-description-7>

---

**QUESTION 2**

After installing a supported OS from a bootable ISO on an MX740c sled, an administrator discovers that not all the hardware is property detected by the OS. They plan to reinstall the OS. What should the administrator do to resolve this issue through OS installation?

- A. Update the Dell OS Driver Pack and use the OS Deployment feature
- B. Modify the bootable ISO to remove faulty drivers and boot directly from the bootable ISO
- C. Modify the bootable ISO to remove faulty drivers and use the OS deployment feature
- D. Update the Dell OS Driver Pack and boot directly from the bootable ISO

Correct Answer: D

---

**QUESTION 3**

DRAG DROP

Match each deployment logical block with its attributes.

Select and Place:

<u>Logical Block:</u>	<u>Attributes:</u>
Network	BIOS, RAID, NIC, iDRAC
Server Template	WWN, WWPN, Virtual MAC Address
Server Configuration Profile	VLAN, QoS
Virtual I/O Pool	Server Template, Virtual I/O Pool and Network

Correct Answer:

<u>Logical Block:</u>	<u>Attributes:</u>
	Server Configuration Profile
	Virtual I/O Pool
	Network
	Server Template

**QUESTION 4**

An administrator is connecting two MX840c to an MX5016s. The MX5016s is configured in Enclosure Assigned mode. What should the requirements of this mode be to avoid configuration issues?

- A. MX745P with a cluster aware OS
- B. MX745P with no OS restrictions
- C. HBA330MMZ with no OS restrictions
- D. HBA330MMZ with a cluster aware OS

Correct Answer: A

Reference: [https://i.dell.com/sites/csdocuments/Product\\_Docs/en/poweredge-mx5016s-mx5000s-technical-guide.pdf](https://i.dell.com/sites/csdocuments/Product_Docs/en/poweredge-mx5016s-mx5000s-technical-guide.pdf) (p.10)

**QUESTION 5**

What can be used as the firmware update source for OME-M within an MX chassis?

- A. Server Update Utility Baseline from a Catalog
- B. Server Update Utility System Live Image (SLI)
- C. Dell Update package System Live Image (SLI)
- D. Dell Update Package Baseline from a Catalog

Correct Answer: D

Reference: [https://topics-cdn.dell.com/pdf/openmanage-enterprise-modular-v10001-poweredge-mx7000\\_users-guide4\\_en-us.pdf](https://topics-cdn.dell.com/pdf/openmanage-enterprise-modular-v10001-poweredge-mx7000_users-guide4_en-us.pdf)

[DES-4421 PDF Dumps](#)

[DES-4421 VCE Dumps](#)

[DES-4421 Study Guide](#)