

# DES-4421<sup>Q&As</sup>

Specialist - Implementation Engineer, PowerEdge MX Modular Exam

**Pass EMC DES-4421 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/des-4421.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

An MX7000 administrator has been tasked to create a Scalable Fabric Architecture on a 3 chassis setup using Fabric B. Which IOM configuration is recommended?

- A. Chassis 1 - Slot B1: MX9116n; Slot B2: MX9116n Chassis 2 - Slot B1: MX5108n; Slot B2: MX5108n Chassis 3 - Slot B1: MX5108n; Slot B2: MX5108n
- B. Chassis 1 - Slot B1: MX7116n; Slot B2: MX7116n Chassis 2 - Slot B1: MX7116n; Slot B2: MX7116n Chassis 3 - Slot B1: MX9116n; Slot B2: MX9116n
- C. Chassis 1 - Slot B1: MX9116n; Slot B2: MX7116n Chassis 2 - Slot B1: MX7116n; Slot B2: MX9116n Chassis 3 - Slot B1: MX7116n; Slot B2: MX7116n
- D. Chassis 1 - Slot B1: MX9116n; Slot B2: MX5108n Chassis 2 - Slot B1: MX5108n; Slot B2: MX9116n Chassis 3 - Slot B1: MX5108n; Slot B2: MX5108n

Correct Answer: A

---

**QUESTION 2**

What is the benefit of C22 power inlet connectors on the MX7000 chassis?

- A. Meet higher power requirements
- B. C22 connectors are now standard on PowerEdge
- C. Allow for higher exhaust temperatures
- D. Enable linking together power supplies

Correct Answer: A

Reference: [https://i.dell.com/sites/csdocuments/Product\\_Docs/en/dell\\_emc\\_poweredge\\_mx7000\\_technical\\_guide.pdf](https://i.dell.com/sites/csdocuments/Product_Docs/en/dell_emc_poweredge_mx7000_technical_guide.pdf)

---

**QUESTION 3**

In an MX7000, which components are cooled by the rear fans?

- A. Fabric A, B, and C IOMs only
- B. All compute and storage sleds
- C. Management Modules only
- D. Fabric A, B, and C IOMs and the Management Modules

Correct Answer: D

Reference: <http://bladesmadesimple.com/2018/08/a-first-look-at-the-dell-emc-poweredge-mx/>

---

**QUESTION 4**

DRAG DROP

A technician is deploying a new MX7000 chassis using the Chassis Deployment Wizard.

What is the correct order o steps followed by the wizard?

Select and Place:

Configure iDRAC and IOM Quick Deploy Settings	STEP 1
Import Profile or join Multi-chassis Group	STEP 2
Configure Activity and Alerts	STEP 3
Define Groups	STEP 4
Update Firmware and configure Proxy	STEP 5

Correct Answer:

	Import Profile or join Multi-chassis Group
	Configure Activity and Alerts
	Configure iDRAC and IOM Quick Deploy Settings
	Update Firmware and configure Proxy
	Define Groups

**QUESTION 5**

DRAG DROP

An administrator is using the OME-M GUI to change the hostname on an unconfigured I/O module inserted in slot A1. They log on to the MX7000 chassis home page.

What is the correct order of steps the administrator should take to set the management IP address?

Select and Place:

Click Apply	STEP 1
Edit the hostname field	STEP 2
Select IOM-A1 in the list	STEP 3
Select Settings and then Management	STEP 4
Select Devices > I/O Modules	STEP 5

Correct Answer:

	Select Devices > I/O Modules
	Select IOM-A1 in the list
	Select Settings and then Management
	Click Apply
	Edit the hostname field

[Latest DES-4421 Dumps](#)

[DES-4421 Practice Test](#)

[DES-4421 Exam Questions](#)