

H12-222^{Q&As}

HCIP-Routing & Switching-IENP V2.5

Pass Huawei H12-222 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/h12-222.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

MPLS VPN is used to solve some limitations of traditional VPN technology. Which are the major limitation that MPLS VPN solves?

- A. Private routes cannot communicate with each other.
- B. Leased lines are expensive.
- C. Bandwidth resources cannot be fully used.
- D. The address space is overlapping.

Correct Answer: D

QUESTION 2

Which of the following parameters is optional when you configure a RADIUS server template on a Huawei switch?

- A. Authentication server IP address and port
- B. Automatic RADIUS user detection
- C. Accounting server address and port
- D. Shared-key

Correct Answer: B

QUESTION 3

When hosts and servers in the same zone communicate with each other, NAT is not required.

- A. TRUE
- B. FALSE

Correct Answer: A

QUESTION 4

Man-in-the-middle attacks or IP/MAC Spoofing attacks are common on intranets and will cause information leakage. Which configuration method can prevent these attacks?

- A. Configure the trusted or untrusted interface.
- B. Limit the maximum number of MAC addresses that can be learned on a switch interface.
- C. Configure DHCP snooping to check the CHADDR field carried in a DHCP Request packet.

D. Configure association between DHCP snooping and IPSP or DAI on the switch.

Correct Answer: ABC

QUESTION 5

Which of the following statements regarding the physical topology monitoring function of eSight are true? (Multiple Choice)

- A. eSight displays the layout and status of NEs, subnets, and links on the GUI.
- B. eSight supports visualized monitoring of the network-wide running status.
- C. eSight displays the architecture of the entire network and relationship between network entities.
- D. The physical topology monitoring provides an entry for unified network monitoring, improving OandM efficiency.

Correct Answer: ABCD

[Latest H12-222 Dumps](#)

[H12-222 Exam Questions](#)

[H12-222 Braindumps](#)