

# HCE-5710<sup>Q&As</sup>

Architecting Hitachi Data Systems Certified Expert - Replication solutions

**Pass Hitachi HCE-5710 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hce-5710.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



### QUESTION 1

A customer wants to use TrueCopy Asynchronous to copy databases to a data center 200km away from the primary site. The applications for these databases have very severe SLAs. Which two factors must be considered? (Choose two.)

- A. All data volumes must be controlled by a file system.
- B. All data volumes in the target storage unit must be offline.
- C. All data volumes in the database must be in the same Consistency Group.
- D. All data volumes in the database must be on the same type of RAID to ensure good performance.

Correct Answer: BC

---

### QUESTION 2

An Hitachi Data Systems customer is planning to use HiCommand Device Manager (HDvM) to manage their TrueCopy pairs on a Universal Storage Platform. Which two are required before TrueCopy pairs can be created with HiCommand Device Manager? (Choose two.)

- A. The P-VOL must be defined as a Command Device.
- B. The HDvM host agent must be installed on the CCI server(s).
- C. The MCU-RCU path must be defined using the Storage Navigator.
- D. The HORCM configuration files must be created on the CCI server.

Correct Answer: BC

---

### QUESTION 3

A customer is replicating data between sites using Universal Replicator. The Universal Replicator Command Control Interface (CCI) device group name is UR\_db01. A power outage occurred at the production site and the users have moved to the recovery site. The production disk array, CCI server, and network equipment are still running on generator power. Which command should the customer issue from the recovery CCI server to suspend the Universal Replicator pairs and reverse the replication direction?

- A. horctakeover -g UR\_db01 -S
- B. pairsplit -g UR\_db01 -swapp
- C. pairsplit -g UR\_db01 -swaps
- D. horctakeover -g UR\_db01 -swapp

Correct Answer: A

---

**QUESTION 4**

A customer has a number of applications on different operating systems. These applications require fail-over capability. The customer has chosen the appropriate cluster technology for each platform. With which two cluster types is Hitachi Data Systems allowed to integrate? (Choose two.)

- A. Sun Cluster
- B. MetroCluster
- C. Veritas Cluster
- D. Continental Cluster

Correct Answer: AC

---

**QUESTION 5**

A customer wishes to create copies of a database using ShadowImage on an Adaptable Modular Storage (AMS) system. Which three products would be used to accomplish this? (Choose three.)

- A. Storage Navigator Modular
- B. Command Control Interface (CCI)
- C. HiCommand Device Manager (HDvM)
- D. HiCommand Replication Monitor (HRpM)
- E. HiCommand Storage Services Manager (HSSM)

Correct Answer: ABC

[Latest HCE-5710 Dumps](#)

[HCE-5710 PDF Dumps](#)

[HCE-5710 VCE Dumps](#)