

HP0-S41^{Q&As}

Building HP Server Solution

Pass HP HP0-S41 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hp0-s41.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

Which feature on the ProLiant Gen9 servers allows a customer to protect the operating system from malware by performing a verification of each component?

- A. HP Smart Memory
- B. RBSU Boot settings
- C. RBSU Digitally Signed Program
- D. UEFI SecureBoot

Correct Answer: D

QUESTION 2

What can be used to modify settings such as power management and boot order on HP ProLiant Servers?

- A. HP Intelligent Provisioning
- B. HP Virtual Connect Manager
- C. HP iLO Federation
- D. ROM-Based Setup Utility

Correct Answer: D

QUESTION 3

A customer needs to add a GPU card to an HP Blade server. What does the customer need to do in order to add the GPU card?

- A. Enable the PCI pass-thru on the Blade server.
- B. Install a PCI riser card in Mezzanine Slot 3 within the Blade server.
- C. Install a PCI Expansion blade in the slot adjacent to the Blade server.
- D. Enable the PCI pass-thru on the Onboard Administrator.

Correct Answer: A

QUESTION 4

What is required for Windows 2012 R2 to boot a GPT-enabled partition greater than 2.2 TB?

- A. Both UEFI and Legacy BIOS enabled on the system

- B. Legacy BIOS enabled on the system
- C. UEFI enabled on the system
- D. NVMe-enabled SSD hard drives

Correct Answer: A

QUESTION 5

You need to manage a C7000 enclosure with HP OneView, but the Virtual Connect modules in the enclosure do not meet the minimum firmware requirements. What should you do to manage the enclosure?

- A. Add an enclosure to HP OneView so that the firmware will be automatically updated to the latest version.
- B. Replicate firmware from the Virtual Connect modules with the minimum supported firmware.
- C. Upload the latest Virtual Connect firmware to the Onboard Administrator and let the Virtual Connect modules automatically update the firmware.
- D. Update the Virtual Connect modules using the Virtual Connect Support Utility (VCSU) before adding the enclosure to HP OneView.

Correct Answer: D

[HP0-S41 PDF Dumps](#)

[HP0-S41 VCE Dumps](#)

[HP0-S41 Practice Test](#)