

HPE2-Z40^{Q&As}

Delta - Applying Aruba Switching Fundamentals for Mobility

Pass HP HPE2-Z40 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hpe2-z40.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A network administrator needs to reach an ArubaOS switch CU at a management IP address. The administrator also needs to ensure that the switch entirely rejects Telnet and SSH connections from users in data VLANs.

How can the administrator meet these goals?

- A. Configure the management IP address on the default VLAN and set a manager password.
- B. Configure the management IP address on a VTY interface and bind an ACL to this interface.
- C. Configure the management IP address on any VLAN except the default VLAN. Set a manager and operator password .
- D. Configure the management IP address on the OOBM port and configure the switch to listen for Telnet and SSH only on this port.

Correct Answer: D

QUESTION 2

A network administrator wants to form a cluster with several Aruba Instant APs (IAPs). What must the administrator verify?

- A. that all APs are pre-configured with WLANs with the same SSID
- B. that all APs are operating on the same radio channel
- C. that all APs are the same model
- D. that all APs are connected in the same subnet

Correct Answer: A

QUESTION 3

What is one requirement to combine Aruba 5400R z|2 Series switches in a Virtual Switching Framework (VSF) fabric?

- A. Both of the members must have two management modules.
- B. The switches must operate in v3-module only mode; any modules of an earlier version are automatically disabled.
- C. The interfaces assigned to the VSF link must be pre-configured as part of a link aggregation.
- D. One of the switches must be an Aruba 5412R switch, while the other member can be any switch in the 5400R series.

Correct Answer: D

QUESTION 4

A company has a cluster of Aruba Instant APs (IAPs). The company wants to add a new IAP to the cluster.

What should network administrators ensure before they connect the new IAP?

- A. that the DHCP server has the correct options 60 and 43
- B. that the new IAP has been provisioned with an IP address and the IP address of the cluster virtual controller (VC)
- C. that Aruba Activate is configured with provisioning rules for the IAP
- D. that the switch port for the AP is untagged for the same VLAN as the current cluster

Correct Answer: A

QUESTION 5

An Aruba Virtual Switching Framework (VSF) fabric has 10GbE interfaces assigned to its VSF link. The network administrator wants to change the link to use 40GbE interfaces.

Which procedure follows the best practices and requirements to set up the VSF links?

- A. Shut down the standby member, remove the VSF link, and then re-create the link with only 40GbE interfaces.
- B. Add the 40GbE interfaces to the VSF link, and then remove the 10GbE interfaces from the link. Create an LACP link aggregation on the 40GbE interfaces, and then add them to the VSF link.
- C. Create a second VSF link that uses the 40GbE interfaces, and then remove the first VSF link.

Correct Answer: A

[HPE2-Z40 PDF Dumps](#)

[HPE2-Z40 VCE Dumps](#)

[HPE2-Z40 Braindumps](#)