

HPE6-A29^{Q&As}

Aruba Certified Mobility Professional 6.4

Pass HP HPE6-A29 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/hpe6-a29.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

When does a RAP's backup SSID begin broadcasting?

- A. When the GRE tunnel to the controller is established.
- B. When the IPsec tunnel to the controller is established.
- C. When the controller cannot be reached with PAPI
- D. When bridging is required for guest users.
- E. When the controller cannot be reached with SSL

Correct Answer: C

QUESTION 2

How is an AP redirected to a Local controller after DNS resolution returns the Master's IP address?

- A. Master looks at the AP-Group and CONTROLLER-IP attributes
- B. Master looks at the AP-Group and LMS-IP attributes
- C. In the AP-provisioning screen, the LMS-IP attribute must be set
- D. The AP must be statically configured to find the local controller
- E. In the AP-provisioning screen, set the CONTROLLER-IP attribute

Correct Answer: B

QUESTION 3

An administrator configures a Virtual AP (VAP) profile for an AP Group Which profiles must the administrator reference in the VAP configuration so that the VAP is functional and the WLAN can be used to connect wireless users to the network? (Select two.)

- A. AAA
- B. Radio Settings
- C. SSID
- D. VLAN Profile
- E. System Profile

Correct Answer: AC

QUESTION 4

The Aruba controller's Command Line Interface can be accessed from WITHIN the browser based Web User Interface using which method?

- A. It's not possible to access the CLI from within the WebUI
- B. Embedded Telnet client
- C. Java based SSH client
- D. Proprietary serial over Ethernet client

Correct Answer: C

QUESTION 5

An administrator wants to use the OS fingerprinting feature to apply users' roles during pre-authentication. However, many of the devices the administrator wants to fingerprint require HTTP packet examination.

Which firewall setting must the administrator enable on the Aruba Mobility controller to perform this type of examination?

- A. Deep Packet inspection (DPI)
- B. Web Content Classification (WCC)
- C. HTTP Payload Inspection (HPI)
- D. Source NAT (SNAT)

Correct Answer: D

[HPE6-A29 PDF Dumps](#)

[HPE6-A29 Study Guide](#)

[HPE6-A29 Exam Questions](#)