

JN0-1301^{Q&As}

Data Center Design, Specialist (JNCDS-DC)

Pass Juniper JN0-1301 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/jn0-1301.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Your data center uses an Ethernet fabric solution for the infrastructure switches.

You must design a redundancy solution that addresses how the servers connect to the members of the Ethernet fabric. Which two statements are true in this scenario? (Choose two.)

- A. It is necessary to use MC-LAG.
- B. You should connect each server to one member with a two-interface LAG.
- C. You should connect each server to two different members.
- D. It is not necessary to use MC-LAG.

Correct Answer: CD

QUESTION 2

You are implementing a Virtual Chassis Fabric using QFX5110 devices.

Which two statements are true in this scenario according to Juniper Networks recommendations? (Choose two.)

- A. Spine devices must assume the RE role.
- B. Leaf devices must have a direct link to all other leaf devices.
- C. Spine devices must assume the line card role.
- D. Leaf devices must have a direct link to all spine devices.

Correct Answer: AD

QUESTION 3

You plan to deploy a set of SRX Series devices in an active/active chassis cluster with an active/active network infrastructure.

Which two statements are true in this scenario? (Choose two.)

- A. This deployment scenario is recommended when firewall services are used extensively for east-west traffic.
- B. End-host traffic is serviced through one SRX node during non-failure conditions.
- C. This deployment scenario is recommended when firewall services are used extensively for north-south traffic.
- D. End-host traffic is serviced through both SRX nodes during non-failure conditions.

Correct Answer: AD

QUESTION 4

Which two characteristics describe the deployment of high-density chassis switches in a data center? (Choose two.)

- A. In EoR deployments, the switches are consolidated in one location.
- B. The switches consume a great deal of power, cooling, and space.
- C. In ToR deployments, the switches provide more port connections, but with lower speeds.
- D. More switches are often needed to accommodate the number of server connections.

Correct Answer: BD

QUESTION 5

Your company is deploying a private cloud based on OpenStack and has selected Contrail Networking as its SDN controller. Which two statements are true in this scenario? (Choose two.)

- A. Underlay tunnels are established between virtualized and bare-metal servers.
- B. MPLS over UDP tunnels are supported.
- C. Overlay tunnels are established between virtualized and bare-metal servers.
- D. MPLS over GRE tunnels are supported.

Correct Answer: CD

[JN0-1301 PDF Dumps](#)

[JN0-1301 Study Guide](#)

[JN0-1301 Exam Questions](#)