

JN0-333^{Q&As}

Security, Specialist (JNCIS-SEC)

Pass Juniper JN0-333 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/jn0-333.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



QUESTION 1

What are the maximum number of supported interfaces on a vSRX hosted in a VMware environment?

- A. 12
- B. 3
- C. 10
- D. 4

Correct Answer: A

QUESTION 2

What are the maximum number of redundancy groups that would be used on a chassis cluster?

- A. The maximum number of redundancy groups use is equal to the number of configured physical interfaces.
- B. The maximum number of redundancy groups use is equal to one more than the number of configured physical interfaces.
- C. The maximum number of redundancy groups use is equal to the number of configured logical interfaces.
- D. The maximum number of redundancy groups use is equal to one more than the number of configured logical interfaces.

Correct Answer: C

QUESTION 3

Click the Exhibit button.

```
[edit]
user@host# show security policies
from-zone red to-zone blue {
    policy deny-http {
        match {
            source-address any;
            destination-address any;
            application junos-https;
        }
        then {
            deny;
        }
    }
}
from-zone red to-zone blue{
    policy default-permit {
        match {
            source-address any;
            destination-address any;
            application any;
        }
        then {
            permit;
        }
    }
}

[edit]
user@host# run show security flow status
Flow forwarding mode:
Inet forwarding mode: packet based (reboot needed to change to flow based)
Inet6 forwarding mode: drop
MPLS forwarding mode: drop
ISO forwarding mode: drop
Flow trace status
Flow tracing status: off
Flow session distribution
Distribution mode: RR-based
Flow ipsec performance acceleration: off
Flow packet ordering
Ordering mode: Hardware
```

You notice that your SRX Series device is not blocking HTTP traffic as expected. Referring to the exhibit, what should you do to solve the problem?

- A. Commit the configuration.
- B. Reboot the SRX Series device.
- C. Configure the SRX Series device to operate in packet-based mode.
- D. Move the deny-http policy to the bottom of the policy list.

Correct Answer: B

QUESTION 4

You must verify if destination NAT is actively being used by users connecting to an internal server from the Internet.

Which action will accomplish this task on an SRX Series device?

- A. Examine the destination NAT translations table.
- B. Examine the installed routes in the packet forwarding engine.
- C. Examine the NAT translation table.
- D. Examine the active security flow sessions.

Correct Answer: A

QUESTION 5

You have recently configured an IPsec tunnel between two SRX Series devices. One of the devices is assigned an IP address using DHCP with an IP address that changes frequently. Initial testing indicates that the IPsec tunnel is not working. Troubleshooting has revealed that Phase 1 negotiations are failing.

Which two actions would solve the problem? (Choose two.)

- A. Verify that the device with the IP address assigned by DHCP is the traffic initiator.
- B. Verify that VPN monitoring is enabled.
- C. Verify that the IKE policy is configured for aggressive mode.
- D. Verify that PKI is properly configured.

Correct Answer: AC

[Latest JN0-333 Dumps](#)

[JN0-333 PDF Dumps](#)

[JN0-333 VCE Dumps](#)