

# JN0-662<sup>Q&As</sup>

Service Provider Routing and Switching - Professional (JNCIP-SP)

## Pass Juniper JN0-662 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass2lead.com/jn0-662.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers





#### **QUESTION 1**

Which two routes use a proper route distinguisher? (Choose two.)

A. 192.168.0.1:12:10.1.0.0/16

B. 12345:12:10.1.0.0/16

C. 192.168.0.1:10.1.0.0:12/16

D. 12345:10.1.0.0:12/16

Correct Answer: AB

#### **QUESTION 2**

Click the Exhibit button.

```
user@host# show protocols ospf
area 0.0.0.6 {
    nssa {
        default-lsa {
            default-metric 10;
            metric-type 1;
            type-7;
        }
no-summaries;
    }
}
```

Referring to the ABR configuration shown in the exhibit, which two statements are correct? (Choose two.)

- A. The ABR advertises a default route to the NSSA with a metric of 10.
- B. To reach the ABR, routers within the NSSA add 10 to their calculated path cost.
- C. The ABR advertises NSSA routes to the backbone area with a metric of 10.
- D. To reach the ABR, routers within the NSSA use the metric 10 as their path cost.

Correct Answer: A

You must explicitly configure the ABR to generate a default route when attached to a stub or not-sostubby-area (NSSA). To inject a default route with a specified metric value into the area, you must configure the default-metric option and specify a metric value.

#### **QUESTION 3**

#### https://www.pass2lead.com/jn0-662.html

2024 Latest pass2lead JN0-662 PDF and VCE dumps Download

Which transport mechanism is required for Layer 3 VPNs?

- A. GRE
- B. VXLAN
- C. IPsec
- D. MPLS

Correct Answer: D

#### **QUESTION 4**

Click the Exhibit button.

```
[edit protocols]
user@router# show
pim {
    rp {
        local {
            address 10.1.1.2;
        }
}
```

While logging in to routers on your network, you find the exact configuration shown in the exhibit on multiple devices.

Which multicast RP strategy is being used in this scenario?

- A. embedded-rp
- B. auto-rp
- C. bsr
- D. anycast-rp

Correct Answer: D

#### **QUESTION 5**

To reduce the size of OSPF Area 100, you configure the area with the no-summaries parameter. After committing this configuration change, you notice that an OSPF router in a remote area is no longer receiving Type 5 LSAs from an ASBR in Area 100.

Which statement is true in this scenario?

- A. The ASBR in Area 100 generates Type 5 LSAs, and places them in its own database.
- B. The ASBR in Area 100 generates Type 5 LSAs, and they are translated to Type 7 LSAs.



### https://www.pass2lead.com/jn0-662.html

2024 Latest pass2lead JN0-662 PDF and VCE dumps Download

- C. The ASBR in Area 100 generates Type 5 LSAs, and they are blocked by the ABR.
- D. The ASBR in Area 100 generates Type 5 LSAs, and a virtual link is required for transport to other areas.

Correct Answer: B

JN0-662 VCE Dumps

JN0-662 Practice Test

JN0-662 Braindumps