

JN0-681^{Q&As}

New Data Center, Professional

Pass Juniper JN0-681 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass2lead.com/jn0-681.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

Which EVPN route type prevents BUM traffic from looping back to a multihomed host?

- A. IP prefix route
- B. Ethernet autodiscovery route
- C. Ethernet segment route
- D. inclusive multicast-Ethernet tag route

Correct Answer: B

QUESTION 2

You are asked to design a deployment plan for a large number of QFX Series switches using ZTP. The ZTP deployment plan must ensure all switches are configured with their designated configuration file.

Which DHCP option and suboption combination would be used to accomplish this task?

- A. DHCP option 43 with a suboption of 00
- B. DHCP option 66 with a suboption of 00
- C. DHCP option 66 with a suboption of 01
- D. DHCP option 43 with a suboption of 01

Correct Answer: A

QUESTION 3

You are implementing perimeter security for your data center. You need to inspect all traffic at Layer 7 and ensure the failure of a port or device will not result in an interruption to traffic flows.

In this scenario, which design would satisfy these requirements?

- A. SRX using LAG
- B. MX with MC-LAG
- C. QFX Virtual Chassis
- D. SRX chassis cluster

Correct Answer: D

QUESTION 4

https://www.pass2lead.com/jn0-681.html

2024 Latest pass2lead JN0-681 PDF and VCE dumps Download

What is the purpose of the command shown in the exhibit?

```
[edit protocols 12-learning]
user@switch# show
disable-vxlan-multicast-transit {
    vxlan-multicast-group 239.0.0.1;
}
```

A. to stop the transmission of transit multicast traffic when there are no interested receivers attached to a remote VTEP.

B. to disallow IGMP requests for the group 239.0.0.1 from hosts attached to the local VTEP.

C. to disable the multicast group 239.0.0.1 across the entire VXLAN.

D. to stop the reception of transit multicast traffic when there are no interested receivers attached to the local VTEP.

Correct Answer: A

QUESTION 5

Which two combinations are supported when configuring a Virtual Chassis Fabric? (Choose two.)

A. two spine nodes and 28 leaf nodes

B. four spine nodes and 20 leaf nodes

C. four spine nodes with 16 leaf nodes

D. two spine nodes and 16 leaf nodes

Correct Answer: CD

JN0-681 PDF Dumps

JN0-681 Study Guide

JN0-681 Braindumps