

# JN0-682<sup>Q&As</sup>

Data Center Professional (JNCIP-DC)

## Pass Juniper JN0-682 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/jn0-682.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



### QUESTION 1

You are designing a Layer 3 fabric underlay using EBGP. You will implement an E VPN- signaled VXLAN overlay on the Layer 3 fabric.

In this scenario, what must you do in the underlay to ensure that the VXLAN overlay will be able to function properly?

- A. The underlay should support the PIM protocol
- B. Each device in the underlay should advertise its loopback address
- C. The underlay should be configured with a separate VRF for each potential tenant
- D. The underlay should advertise the host connected interlaces on all leaf device

Correct Answer: B

---

### QUESTION 2

You are configuring a DCI VPN solution between sites that require an L3VPN to work with your EVPN deployment. Your organization's policy restricts configuring RSVP and LDP on your WAN links. While configuring the solution, you notice that no routes exist in the inet table. In this scenario, which parameter will solve this problem?

- A. bgp family inet labeled-unicast per-group-label
- B. bgp family inet labeled-unicast aggregate-label
- C. bgp family inet labeled-unicast resolve-vpn
- D. bgp family evpn signaling

Correct Answer: D

---

### QUESTION 3

A company wants to expect their hosting business and is seeking solutions to supported multiple tenants. Each tenant should be able to configure their own logical interfaces. Also, based on customer needs, all routing features must be supported.

What will satisfy the customer's requirements?

- A. Bridge domains
- B. Tenant systems
- C. Logical systems
- D. Routing instances

Correct Answer: C

---

**QUESTION 4**

Which two statements are true about VRF routing instances? (Choose two.)

- A. VRF can be used in conjunction with Layer 3 logical interfaces.
- B. Each logical Layer 3 interface can belong to only one routing instance.
- C. Each logical Layer 3 interface can belong to multiple routing instances.
- D. VRF does not enable multitenancy.

Correct Answer: AB

---

**QUESTION 5**

Which two statements about ZTP are true? (Choose two.)

- A. The image storage service and the DHCP server can be running on different server hosts.
- B. When a switch is booted, DHCP requests are sent only through the management Ethernet interface.
- C. The image storage service must be running on the same server host where the DHCP service is running.
- D. When a switch is booted, DHCP requests are sent through the management interface as well as attached revenue ports.

Correct Answer: AB

[JN0-682 PDF Dumps](#)

[JN0-682 Practice Test](#)

[JN0-682 Braindumps](#)