

NS0-173^{Q&As}

Cisco and NetApp FlexPod Design Specialist

Pass NetApp NS0-173 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/ns0-173.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A FlexPod administrator is building a WWN pool for a server that has 33 ports. In this scenario, what is the smallest size possible for the pool?

- A. 33
- B. 34
- C. 68
- D. 66

Correct Answer: D

QUESTION 2

A customer is configuring the UCS to handle a multitenant environment. The customer has created an organization within UCS for each tenant and would like to allow access to these organizations for only users that belong to that tenant.

In this scenario, which feature in UCS Manager should the customer use to accomplish this task?

- A. Locales
- B. Trusted Platform Module
- C. Service Profile
- D. User Roles

Correct Answer: C

Reference: https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ucs-manager/GUI-User-Guides/Admin-Management/3-2/b_Cisco_UCS_Admin_Mgmt_Guide_3_2/b_Cisco_UCS_Admin_Mgmt_Guide_3_2_chapter_01010.html

QUESTION 3

A client has a requirement to set up a FlexPod Datacenter with the NetApp fabric MetroCluster architecture. You want to enable connectivity between the deployments.

In this design, which two components are required to accomplish this task? (Choose two.)

- A. Cisco Nexus 7000 switches
- B. Cisco Nexus 3000 switches
- C. Cisco MDS 9300 switches
- D. Cisco Nexus 9000 switches

Correct Answer: AD

Reference: <https://www.netapp.com/media/12434-nva-0030-design.pdf>

QUESTION 4

An architect is designing a FlexPod environment with Cisco Nexus 5000 switches to SAN boot all of the ESXi hosts over FC.

In this scenario, what should the LUN ID number be?

- A. LUN 2
- B. LUN 3
- C. LUN 0
- D. LUN 1

Correct Answer: C

Reference: https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/UCS_CVDs/flexpod_50_M3.html

QUESTION 5

A customer wants to deploy a FlexPod solution that involves directly connecting the NetApp AFF storage using the FCoE protocol to the Cisco UCS Fabric Interconnects.

In this scenario, which Cisco UCS Fibre Channel mode would be used to accomplish this task?

- A. trunk mode
- B. end host mode
- C. switching mode
- D. access mode

Correct Answer: C

Reference: <https://www.netapp.com/media/16411-nva-0025-deploy.pdf>

[Latest NS0-173 Dumps](#)

[NS0-173 PDF Dumps](#)

[NS0-173 VCE Dumps](#)