

# NS0-175<sup>Q&As</sup>

Cisco and NetApp FlexPod Design Specialist

## Pass NetApp NS0-175 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/ns0-175.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



### QUESTION 1

What are three requirements for all FlexPod Datacenter solutions? (Choose three.)

- A. two NetApp storage controllers in a high-availability (HA) pair configuration
- B. a separate 100 Mbps Ethernet/1 Gbps Ethernet out-of-band management network
- C. a pair of Fabric Extenders in a redundant configuration
- D. two Cisco UCS 6200, 6300, or 6400 Series Fabric Interconnects in a redundant configuration
- E. redundant boot-from-SAN LUN paths

Correct Answer: CDE

---

### QUESTION 2

You are sizing a FlexPod Virtual Desktop solution for a customer with 500 virtual desktops in a shared Remote Desktop Services (RDS) topology.

In this scenario, which Cisco best practice should you use?

- A. You should avoid placing more than 20 users per physical host
- B. You should avoid over-committing physical CPU resources for virtual machines
- C. You should avoid changing the virtual host disk queue depth
- D. You should avoid multiple vCPUs per individual virtual machine

Correct Answer: B

Reference: [https://www.vmware.com/content/dam/digitalmarketing/vmware/en/pdf/techpaper/View51\\_on\\_FlexPod\\_Design\\_Guide.pdf](https://www.vmware.com/content/dam/digitalmarketing/vmware/en/pdf/techpaper/View51_on_FlexPod_Design_Guide.pdf)

---

### QUESTION 3

A customer wants to upgrade their core fabric between each site with a modular chassis switch that supports up to 400GbE per port to accommodate more business transaction volume.

In this scenario, which device would help them accomplish their objective?

- A. Cisco Nexus 9504
- B. Cisco Nexus 9332C
- C. Cisco MDS 9706

D. Cisco Catalyst 9400

Correct Answer: A

Reference: <https://www.cisco.com/c/en/us/solutions/data-center/high-capacity-400g-data-centernetworking/index.html>

---

#### QUESTION 4

An administrator wants to ensure secure authentication while accessing a NetApp ONTAP system.

In this scenario, which two access methods should be used? (Choose two.)

A. RSH

B. SSH

C. HTTPS

D. HTTP

Correct Answer: AB

Reference: <https://www.netapp.com/fr/media/10674-tr4569.pdf>

---

#### QUESTION 5

You want to direct-connect NetApp storage to a UCS Mini over IP. In this scenario, which storage protocol is supported?

A. CIFS

B. FC

C. S3

D. iSCSI

Correct Answer: B

Reference: [https://www.cisco.com/c/dam/en/us/td/docs/unified\\_computing/ucs/UCS\\_CVDs/flexpod\\_ucsmmini\\_design.pdf](https://www.cisco.com/c/dam/en/us/td/docs/unified_computing/ucs/UCS_CVDs/flexpod_ucsmmini_design.pdf)

[NS0-175 VCE Dumps](#)

[NS0-175 Exam Questions](#)

[NS0-175 Braindumps](#)