

# NS0-527<sup>Q&As</sup>

NetApp Certified Implementation Engineer - Data Protect

## Pass NetApp NS0-527 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/ns0-527.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by NetApp  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



#### QUESTION 1

Your customer needs to activate a destination SVM DR following a disaster. In this situation, which two actions should be performed? (Choose two.)

- A. Shut down the source cluster.
- B. From the destination cluster, break the SVM DR relationship.
- C. From the source cluster, break the SVM DR relationship.
- D. Start the destination SVM.

Correct Answer: AD

---

#### QUESTION 2

You are the administrator of an ONTAP cluster, where the majority of users are using Linux machines with home directories mounted using NFS. You keep six daily, four weekly, and one monthly Snapshot copy locally. However, you do not replicate the data to another instance of ONTAP. One of your users reports having accidentally deleted a file, but does not remember the self-serve restore procedure.

How does the user restore the file without having administrator privileges on the cluster?

- A. Issue the snapshot restore-file command.
- B. Copy the deleted file from the .snapshot directory.
- C. Issue the volume snapshot restore command.
- D. Using ONTAP System Manager, restore the volume from a Snapshot copy.

Correct Answer: B

---

#### QUESTION 3

Which two NetApp technologies allow for synchronous replication of data between two remote sites? (Choose two.)

- A. SyncMirror
- B. SnapVault
- C. Metro Cluster
- D. SnapMirror

Correct Answer: BD

---

#### QUESTION 4

When installing a new AFF A700s, you notice that the HA interconnect adapters use miniSAS HD. You subsequently consult Hardware Universe to find out that only 0.5M cables are supported. Due to the importance of the system data fields

that use this link, you delay the installation until you can acquire 0.5M cables.

In this scenario, which two system data fields are communicated between HA pairs over the interconnect adapters? (Choose two.)

- A. NVRAM mirroring
- B. heartbeat signal
- C. intercluster peering
- D. data LIF location

Correct Answer: AC

---

#### QUESTION 5

Which two configurations would be used to protect volumes in a production ONTAP system at two different disaster recovery (DR) locations? (Choose two.)

- A. SnapMirror in a fan-out topology
- B. SVM DR in a cascade topology
- C. SnapMirror in a cascade topology
- D. SVM DR in a fan-out topology

Correct Answer: AB

[Latest NS0-527 Dumps](#)

[NS0-527 PDF Dumps](#)

[NS0-527 VCE Dumps](#)