

4A0-M05^{Q&As}

Nokia Cloud Packet Core

Pass Nokia 4A0-M05 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/4a0-m05.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

Which of the following statements regarding CMM log management is FALSE?

- A. VMs push logs to the Kafka pipeline.
- B. The event consumer in NECC retrieves the logs from Kafka.
- C. Various log files generated automatically in CMM.
- D. A log query can be created to retrieve logs from the database based on a time range.

Correct Answer: B

QUESTION 2

Which of the following statements about CMG VNF scaling is TRUE?

- A. OAM-VM can be scaled out in steps of a single VM for CMG LB mode deployment
- B. LB-VM can be scaled out in steps of a single VM for CMG LB-less mode deployment
- C. MG-VM can be scaled out in steps of an MG-VM pair for CMG LB mode deployment
- D. LB-VM and MG-VM must be scaled simultaneously to achieve a successful CMG deployment

Correct Answer: D

QUESTION 3

Based on the exhibit output, which of the following statements is TRUE?

```
=A:CMG2-Pod1# show vm-function
```

```
=====
```

```
VM Function Summary
```

```
=====
```

VM Id	Id	Provisioned Type Equiped Type (if different)	Admin State	Operational State
1	1	m20-v	up	up
	2	isa-ip-reas-v isa-ms-v	up	up
3	1	isa-mg-v isa-ms-v	up	up
	2	(not provisioned) isa-ms-v	up	unprovisioned

```
=====
```

- A. This CMG has one LB VM and one MG VM.
- B. This CMG has one LB VM and two MG VMs.
- C. This CMG has two LB VM and one MG VM.
- D. This CMG has two LB VM and two MG VMs.

Correct Answer: A

QUESTION 4

Which of the following lifecycle management operations is NOT supported by CMM?

- A. Healing of all CMM VMs
- B. Scale out of CPPS, PAPS, and IPPS VMs
- C. Scale in of NECC and IPDS VMs
- D. Instantiation of all CMM VMs

Correct Answer: C

QUESTION 5

Which of the following statements about networks used by CMG is FALSE?

- A. A management network used for CMG management
- B. Data switch fabric is used to carry signaling messages between LB-VMs and OAM-VMs

- C. Control switch fabric is used to carry inter-VM control messaging
- D. External networks are used to carry both control plane and user plane traffic

Correct Answer: A

QUESTION 6

Which of the following statements regarding CMM external networks is FALSE?

- A. External networks terminating on IPDS carry LTE signaling traffic.
- B. External networks terminating on IPPS carry 3G user plane traffic.
- C. External networks terminating on PAPS carry 3G signaling traffic.
- D. External networks terminating on PAPS carry 2G user plane traffic.

Correct Answer: D

QUESTION 7

Which of the following about CMG configuration management is FALSE?

- A. CMG can be configured using CLI commands
- B. CMG can be configured using SNMP interfaces
- C. CloudBand Infrastructure Software (CBIS) is used for CMG out-of-band management
- D. CMG OAM-VM provides system configuration, system assurance, and alarm management

Correct Answer: B

QUESTION 8

Which of the following statements about 4G-5G CN-level interworking solution is FALSE?

- A. It requires a direct interface between the two radio nodes serving the UE
- B. The UE manages the LTE and NR interface connections independently
- C. The UE can be registered to both EPC and next generation core
- D. The UE IP address remains the same despite changes in the network that the UE connects to

Correct Answer: D

QUESTION 9

Which of the following statements regarding the CMM virtual network function (VNF) architecture is FALSE?

- A. The CMM VNF consists of multiple virtual machines that run on top of a cloud infrastructure.
- B. The load balancer layer terminates external logical interfaces.
- C. The transaction layer processes 3G user plane.
- D. The CMM VNF follows a multi-tier architecture where each tier can scale independently.

Correct Answer: A

QUESTION 10

Which of the following statements regarding CMM deployment is FALSE?

- A. Hyperthreading and CPU pinning are enabled.
- B. An anti-affinity rule is used to ensure NECC VMs are deployed on different servers.
- C. Two availability zones are required for a successful CMM deployment.
- D. SR-IOV and DPDK are used to accelerate packet processing.

Correct Answer: D

[Latest 4A0-M05 Dumps](#)

[4A0-M05 Practice Test](#)

[4A0-M05 Exam Questions](#)