![Pass2Lead https://Pass2Lead.com]

HC-711-ENU^{Q&As}

HCNA Huawei Certified Network Associate - Constructing Basic Security Network (HCNA-CBSN) - ENU

Pass Huawei HC-711-ENU Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass2lead.com/hc-711-enu.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

Active attacks focused prevention, rather than detection, for such attacks are generally uses encryption technology to protect the confidentiality of the information

A. True

B. False

Correct Answer: B

QUESTION 2

Which of the following products can be achieved on NAT audit log management?

A. TSM

B. DSM

C. eLog

D. VSM

Correct Answer: C

QUESTION 3

Meaning Trunk Access Port PVID value and significance of the port PVID bit different, in Access represents the value of the default VLAN, but said the port belongs to the VLAN Trunk actually.

A. True

B. False

Correct Answer: B

QUESTION 4

After the write function is enabled USB encryption policies, end-user copy to U disk files are encrypted, only the enterprise user and installed TSM terminal security agents in order to use these encrypted files, encrypted files copied from disk to the local U hardware automatically decrypted;

A. True

B. False

Correct Answer: A

QUESTION 5

About the VLAN tag processing, the following description of the error is?

A. When Trunk port receives a frame,if the frame does not contain 802.1Q tag header, will be marked with PVID port; If the frame contains the 802.1Q tag header, no change.

B. When Trunk port to send the frame,when the port\\'s PVID VLAN ID of the frame is not the same,discarded; When PVID VLAN ID and port with the same time frame,the pass-through

C. When Access port receives a frame,if the frame does not contain 802.1Q tag header, will be marked with PVID port; If the frame contains the 802.1Q tag header, the switch does not deal with them directly discarded.

D. When Access port to send frames,stripping 802.1Q tag header, frame issued ordinary Ethernet frames

Correct Answer: B

QUESTION 6

LNS through what information (protocol field) to determine the packet as L2TP packet and sent L2TP protocol processing module for processing?

A. LAC client source IP address

B. The LNS destination IP address

C. Source UDP port 1701

D. UDP port 1701

Correct Answer: D

QUESTION 7

When configuring l2tp, the command start l2tp {ip ip-address, statement is correct? (Choose three)

A. LNS is used to specify the trigger condition to initiate a call

B. LAC is used to specify the trigger condition to initiate a call

C. You can specify the domain name as a trigger condition

D. You can specify the full name as a trigger condition

Correct Answer: BCD

QUESTION 8

When TSM system supports strong linkage anti-virus software, anti-virus software will be able to drive anti-virus and other operations.

A. True

B. False

Correct Answer: A

QUESTION 9

ASPF makes firewall to support multiple data channels of a control on the channel protocol, but also to facilitate the formulation of policies in various security applications are very complex situation.

A. True

B. False

Correct Answer: A

QUESTION 10

For AH and ESP, the following statement is correct? (Choose three)

A. AH provides data integrity and encryption

B. Tunnel mode,AH for the new IP header must verify,so AH IPSEC VPNcannotbe applied in the middle of a situation nat conversion.

C. AH ESP can provide all of the features in addition to data encryption outside

D. Tunnel mode,ESP packets do not verify the new IP header.

Correct Answer: BCD

QUESTION 11

L2TP technology, LAC client uses port number _____ _____ protocol encapsulated packets.

A. TCP 51

B. UDP 51

C. UDP 1701

D. TCP 1701

Correct Answer: C

QUESTION 12

SVN3000 network expansion capabilities, the need to implement remote users can access the corporate network and

local area network, you cannot access the Internet, the client needs to use routing as follows:

A. Full- channel mode (Full Tunnel)

B. Separation channel mode (Split Tunnel)

C. Routing (route Tunnel)

D. Manually (Manual Tunnel)

Correct Answer: B

QUESTION 13

LAC is a device with PPP and L2TP protocol processing capabilities.

A. True

B. False

Correct Answer: A

QUESTION 14

Priority DMZ area is how much?

A. 5

B. 50

C. 85

D. 100

Correct Answer: B

QUESTION 15

IKE negotiation mode include? (Choose two)

A. Master Mode

B. Aggressive Mode

C. Fast mode

D. Transfer mode

Correct Answer: AB

Latest HC-711-ENU Dumps   HC-711-ENU Exam   HC-711-ENU Braindumps
                                        Questions