

# H13-621<sup>Q&As</sup>

HCNP-Storage-CUSN(Constructing Unifying Storage Network)

## Pass Huawei H13-621 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass2lead.com/h13-621.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

OceanStor medium of hard disk storage system scan, by which method?

- A. read hard all sectors in order
- B. the use of hard disk built-in media scan function
- C. use third party software embedded controller
- D. independent development of new analysis software

Correct Answer: B

---

**QUESTION 2**

Which command can be runned to create file system for partitions in Linux.

- A. mkfs.ext3 /dev/sdb
- B. dd if=/dev/sdb of=/dev/zero bs=1024 count=1000
- C. dd if=/dev/zero of=/dev/sdb bs=1024 count=1000
- D. mkfs -N /dev/sdb

Correct Answer: A

---

**QUESTION 3**

OceanStor storage under the condition of a fan module fault, another fan module automatically improve speed, guarantee temperature can controll under single fan module, at this time also need to replace the fault fan in time.

- A. True
- B. False

Correct Answer: A

---

**QUESTION 4**

When Snapshot rolled back, the source LUN must map to the host to use it.

- A. True
- B. False

Correct Answer: B

---

**QUESTION 5**

ISCSI is based on TCP/IP protocol, the default service port is?

- A. 3260
- B. 8088
- C. 8443
- D. 3206

Correct Answer: A

---

**QUESTION 6**

What respect affect random write IOPS from depth size of striping under RAIDs?

- A. IO distribution
- B. read punishment
- C. number of member disk
- D. write punishment

Correct Answer: AD

---

**QUESTION 7**

The FC SAN topology of fiber optic network, which are include? (Select three Answers)

- A. point-to-point
- B. arbitration ring
- C. switching topology
- D. hybrid network

Correct Answer: ABC

---

**QUESTION 8**

For Huawei's storage system, which of the following description of global hot dish is correct? (Select 3 Answers)

- A. after refactoring of hot dish participate in a member disk of RAID group failure, automatically becomes member disk of RAID group, the original fault members disk automatically becomes hot spare disk after replacement for new dish

- B. hot plate uniform distribution, recommend at least 1-2 pieces of hot plate each box
- C. hot dish has no data protection for RAID0
- D. the safe disk cannot be used as hot spare

Correct Answer: BCD

---

**QUESTION 9**

The management mode of ISM integrated storage management software for storage array is the in-band management mode.

- A. True
- B. False

Correct Answer: B

---

**QUESTION 10**

ATA to SATA is actually from serial to parallel shift.

- A. True
- B. False

Correct Answer: B

---

**QUESTION 11**

The most important three part of SAN network in technically: device interfaces (E. g, SCSI, fiber channel and ESC0N, etC. ), connection device (switches, gateway, router and Hub, etC. ) and communication control protocol (E. g iSCSI and FC, etC. ) the three components plus additional storage devices and servers, constructed SAN system from the component, the SAN can be divided into host,HBA, switches, storage devices of the two is not match.

- A. True
- B. False

Correct Answer: B

---

**QUESTION 12**

Which basic functions can log analysis function of maintenance Assistant achieve? (Select 3 answers)

- A. Log import
- B. Log filter

C. Keyword Search

D. Informationcollection

Correct Answer: ABC

---

**QUESTION 13**

For S5000 and S2600 system, DB is configuration information in storage system, intraday record in the safe system, when power up, controller reads the DB. If there is a DB does not agree with other DB, storage will enter in safe mode, equipment can't normal use, need to synchronize the DB information.

A. True

B. False

Correct Answer: A

---

**QUESTION 14**

In FC SAN system, card module of host HBA is responsible for distributing the IO to the storage, what are the four indicators need to focus on?

A. concurrency;IOsize;Bandwidth;IOPS

B. concurrency; IO size; Bandwidth; The response time

C. concurrency;IOsize;Queuedepth;IOPS

D. Theamount of data;IO size;Bandwidth;IOPS

Correct Answer: A

---

**QUESTION 15**

when SAN storage array power up, enter into MML mode, sys status check System Running Status: ( normal mode ) normal mode shows power up successful for the system.If it is not normal mode, can judge power up failure for the system.This judgment method of system startup anomaly is correct.

A. True

B. False

Correct Answer: A

---

[H13-621 VCE Dumps](#)

[H13-621 Practice Test](#)

[H13-621 Braindumps](#)